

CLI MH 70 HSTR**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



CLI M identification markers are slid onto CLI MH carrier strips and secured by means of cable ties. The system is particularly suitable for large conductor and cable cross-sections.

Advantages:

- Combination marker for cable and pipe markers
- One size for all diameters above 16 mm²
- Unrestricted combination options
- Closed, permanently attached markers
- Very good legibility

General ordering data

| | |
|------------|--|
| Version | CableLine, Accessories, 10 - 317 mm, 70 x 11.3 mm, black |
| Order No. | 0524400000 |
| Type | CLI MH 70 HSTR |
| GTIN (EAN) | 4008190075057 |
| Qty. | 100 pièce(s) |

CLI MH 70 HSTR

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Caractéristiques techniques

Dimensions and weights

| | | | |
|------------|---------|-----------------|------------|
| Depth | 3 mm | Depth (inches) | 0,118 inch |
| Height | 70 mm | Height (inches) | 2,756 inch |
| Width | 11,3 mm | Width (inches) | 0,445 inch |
| Net weight | 0,81 g | | |

Temperatures

| | |
|-----------------------------|--------------|
| Operating temperature range | -30...100 °C |
|-----------------------------|--------------|

General data

| | |
|--|----------------------------------|
| Colour | black |
| Material | Polyamide 66 |
| Material colour according to resistance code | 0 |
| Number of markers per combination | 1 Component part = Accessories |
| Number of markers per packaging unit | Form of supply Component part |
| Operating temperature range | -30...100 °C |
| Operating temperature range, max. | 100 °C |
| Operating temperature range, min. | -30 °C |
| Recommended industries | Process, Machinery |
| Type of printing | neutral |
| UL 94 flammability rating | V-0 |
| Version | halogen-free |
| Width | 11,3 mm |

Conductor and cable markers

| | | | |
|-------------------------------|--------------------|----------------------------------|--------------------------|
| Conductor O.D. | 10 - 317 mm | Conductor O.D., max. | 317 mm |
| Conductor O.D., min. | 10 mm | Conductor cross-section, max. | 500 mm ² |
| Conductor cross-section, min. | 16 mm ² | Cross-section for connected wire | 16 - 500 mm ² |

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC001530 | ETIM 7.0 | EC001530 |
| ETIM 8.0 | EC001530 | ETIM 9.0 | EC001530 |
| ECLASS 9.0 | 27-40-04-01 | ECLASS 9.1 | 27-40-06-29 |
| ECLASS 10.0 | 27-40-04-01 | ECLASS 11.0 | 27-28-11-02 |
| ECLASS 12.0 | 27-28-11-02 | ECLASS 13.0 | 27-28-11-02 |
| ECLASS 14.0 | 27-28-11-02 | | |

Environmental Product Compliance

| | |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC | No SVHC above 0.1 wt% |

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|------------|--|
| Catalogues | Catalogues in PDF-format |
|------------|--|

Fiche de données

CLI MH 70 HSTR

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Dessins

Example of use

