

8502SHG2V02S

NEMA Contactor, Type S, nonreversing, Size 6,
540A, 400 HP at 575 VAC, 3 phase, up to 100 kA,
3 pole, 120 V coil, NEMA 1



Principal

Product Type	Contacteur
Product Range	8502S
Contacteur Type	Non inverseur

Complémentaire

NEMA Size	6
Rated Current	540 A
Number of Poles	3P
Maximum Voltage Rating	600 V AC
Phase	3 phases
Horsepower Rating	150 HPà 200 V AC 200 HPà 230 V AC 400 HPà 460 V AC 400 HPà 575 V AC
SCCR	Disjoncteur 800 A maximum, SCCR: 65 kA at 480 V AC Fusible J 600 A maximum, SCCR: 100 kA at 600 V AC Fusible T 600 A maximum, SCCR: 100 kA at 600 V AC Fusible RK1 600 A maximum, SCCR: 100 kA at 600 V AC Fusible RK5 600 A maximum, SCCR: 100 kA at 600 V AC
Coil Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Control Circuit Type	Control circuit transformer
Control Units	No control units
Pilot Light	Sans signalisation
Auxiliary Contacts	Sans
Other Equipment	2 fuses (primary)
Terminal Type	Borniers à vis-étrier

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Height	1670 mm
Width	514 mm
Depth	334 mm

Environnemental

Enclosure Type	NEMA 1 feuille d'acier peint
Certifications	UL listed file E78351 CCN NLDX CSA

Emballage

Poids de l'emballage (Kg)	18,144 kg
---------------------------	-----------

Offre de la durabilité

Régulation REACH	Déclaration REACH
Sans SVHC REACH	Oui
Directive RoHS UE	Non conforme
Régulation RoHS Chine	Déclaration RoHS pour la Chine Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.

Garantie contractuelle

Garantie	18 months
----------	-----------