

# 8538SBW33V02S

NEMA Combination Starter, Type S, 30A fusible disconnect, Size 0, 18A, 5 HP at 600 VAC polyphase, 120VAC coil, NEMA 4/4X



## Principal

Product	Combination Starter
Type	S
Control Circuit Type	Separate control circuit

## Complémentaire

Control Circuit Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Starter Type	Non réversible
Number of Poles	3P
Horsepower Rating	5 hpà 460 V AC, 3 phases 5 hpà 575 V AC, 3 phases
Maximum Voltage Rating	600 V AC
Control Units	No control units
Pilot Light	Sans signalisation
Auxiliary Contacts	Sans
Type de surcharge thermique	Melting alloy 3
Disconnect Type	Fusible disconnect switch, type R fusible, 30 A
Taille NEMA	0

## Environnement

Enclosure Type	NEMA 4/4X acier inoxydable et with external reset
----------------	---

## Emballage

Poids de l'emballage (Kg)	14,928 kg
---------------------------	-----------

## Offre de la durabilité

Régulation REACH	<a href="#">Déclaration REACH</a>
Directive RoHS UE	Non conforme
Régulation RoHS Chine	<a href="#">Déclaration RoHS pour la Chine</a> Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.

## Garantie contractuelle

Garantie	18 months
----------	-----------