



Principal

Product or Component Type	Disjoncteur
Range	PowerPact P
Current Sensor Rating Range	1000 A
Rated Current	1000 A
Breaking Capacity	100 kA à 240 V AC 65 kA à 480 V AC 25 kA à 600 V AC
Trip Unit Technology	Électronique, Puissance, Micrologic 6.0 P, LSIG
AWG Gauge	AWG 3/0...500 kcmil (aluminium / cuivre) pour 4 câble(s)

Complémentaire

Device Short Name	A
Certifications	CEI CSA Listé UL
Rated operational Voltage	600 V AC
Module Type	P-Frame
Mounting Location	Busbar
Mounting Mode	I-Line
Poles Description	3P
Circuit Breaker Rating Code	J
Continuous Current Rating	80 %
Electrical Connection	I-Line connection ligne Cosses charge
Communication Interface	Modbus
Tightening Torque	50 N.m pour 95...240 mm ² (AWG 3/0...500 kcmil) 1,0...1,3 N.m
Height	410,46 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Width	210,06 mm
Depth	204,47 mm

Emballage

Poids de l'emballage (Kg)	14,515 kg
---------------------------	-----------

Offre de la durabilité

Statut environnemental de l'offre	Produit Green Premium
Régulation REACH	Déclaration REACH
Directive RoHS UE	Conforme Déclaration RoHS UE
Sans mercure	Oui
Information sur les exemptions RoHS	Oui
Régulation RoHS Chine	Déclaration RoHS pour la Chine Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.
Profil environnemental	Profil environnemental du Produit
Profil de circularité	Informations de fin de vie
Sans PVC	Oui

Garantie contractuelle

Garantie	18 months
----------	-----------