

8502SGG2V02S

NEMA Contactor, Type S, nonreversing, Size 5, 270A, 200 HP at 575 VAC, 3 phase, up to 100 kA, 3 pole, 120 V coil, NEMA 1



Principal

Product Type	Contacteur
Product Range	8502S
Contacteur Type	Non inverseur

Complémentaire

NEMA Size	5
Rated Current	270 A
Number of Poles	3P
Maximum Voltage Rating	600 V AC
Phase	3 phases
Horsepower Rating	75 HPà 200 V AC 100 HPà 230 V AC 200 HPà 460 V AC 200 HPà 575 V AC
SCCR	Disjoncteur 400 A maximum, SCCR: 100 kA at 480 V AC Fusible J 400 A maximum, SCCR: 100 kA at 600 V AC Fusible T 400 A maximum, SCCR: 100 kA at 600 V AC Fusible RK1 400 A maximum, SCCR: 100 kA at 600 V AC Fusible RK5 400 A maximum, SCCR: 100 kA at 600 V AC
Coil Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Control Circuit Type	Separate control circuit
Control Units	No control units
Pilot Light	Sans signalisation
Auxiliary Contacts	Sans
Other Equipment	Fusible non fourni
Terminal Type	Borniers à vis-étrier

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Height	1123 mm
Width	437 mm
Depth	325 mm

Environnemental

Enclosure Type	NEMA 1 feuille d'acier peint
Certifications	UL listed file E78351 CCN NLDX CSA

Emballage

Poids de l'emballage (Kg)	62,142 kg
---------------------------	-----------

Offre de la durabilité

Régulation REACH	Déclaration REACH
Sans SVHC REACH	Oui
Directive RoHS UE	Non conforme
Régulation RoHS Chine	Déclaration RoHS pour la Chine Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.

Garantie contractuelle

Garantie	18 months
----------	-----------