

# 8536SDA1V02S

NEMA Motor Starter, Type S, nonreversing, Size 2, 45A, 25 HP at 460 VAC, 5 kA SCCR, 3 phase, 3 pole, melting alloy, 120 VAC coil, NEMA 12



## Principal

|               |                  |
|---------------|------------------|
| Product Type  | Démarreur moteur |
| Product Range | S                |
| Starter Type  | Non réversible   |

## Complémentaire

|                        |  |
|------------------------|--|
| NEMA Size              | 2  |
| Rated Current          | 45 A   |
| Number of Poles        | 3P   |
| Maximum Voltage Rating | 600 V AC   |
| Phase                  | 3 phases   |
| Type of Overload       | Melting alloy 3  |
| Horsepower Rating      | 10 HP at 200 V AC<br>15 HP at 230 V AC<br>25 HP at 460 V AC<br>25 HP at 575 V AC |
| SCCR                   | Disjoncteur: 5 kA at 600 V AC<br>Fusible: 5 kA at 600 V AC                       |
| Coil Voltage           | 110 V AC 50 Hz<br>120 V AC 60 Hz   |
| Control Circuit Type   | Separate control circuit   |
| Control Units          | No control units   |
| Pilot Light            | Without pilot light  |
| Auxiliary Contacts     | Sans   |
| Terminal Type          | Borniers à vis-étrier  |
| Height                 | 406,40 mm  |
| Width                  | 206,50 mm  |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|       |           |
|-------|-----------|
| Depth | 235,71 mm |
|-------|-----------|

## Environnement

|                |                               |
|----------------|-------------------------------|
| Enclosure Type | NEMA 12 feuille d'acier peint |
| Certifications | Listé UL<br>CSA<br>NEMA       |

## Emballage

|                           |           |
|---------------------------|-----------|
| Poids de l'emballage (Kg) | 9,752 kg  |
| Hauteur de l'emballage 1  | 27,686 cm |
| Largeur de l'emballage 1  | 25,908 cm |
| Longueur de l'emballage 1 | 42,418 cm |

## Offre de la durabilité

|                                     |  |
|-------------------------------------|--|
| Régulation REACH                    | <a href="#">Déclaration REACH</a>  |
| Directive RoHS UE                   | Conforme<br><a href="#">Déclaration RoHS UE</a>  |
| Sans mercure                        | Oui  |
| Information sur les exemptions RoHS | <a href="#">Oui</a>  |
| Régulation RoHS Chine               | <a href="#">Déclaration RoHS pour la Chine</a><br>Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information. |
| Sans PVC                            | Oui  |

## Garantie contractuelle

|          |           |
|----------|-----------|
| Garantie | 18 months |
|----------|-----------|