

G 20/0.25A/F

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Product image



For protection against overcurrent, we offer cartridge fuse with dimensions 5x20 mm in sizes from 100 mA to 6.3 A.

General ordering data

Version	Miniature fuse, quick-acting, 0.25 A, G-Si. 5 x 20
Order No.	0430500000
Type	G 20/0.25A/F
GTIN (EAN)	4008 19015399 1
Qty.	10 pièce(s)

G 20/0.25A/F**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Caractéristiques techniques**Dimensions and weights**

Depth	5 mm	Depth (inches)	0,197 inch
Height	20 mm	Height (inches)	0,787 inch
Width	5 mm	Width (inches)	0,197 inch
Net weight	0,9 g		

Material data

Colour	Light Grey
--------	------------

System specifications

Version	Fuse accessories
---------	------------------

Fuse cartridges

Cartridge fuse	G-Si. 5 x 20	Characteristics	quick-acting
Colour	Light Grey	Current	0,25 A
Melting integral	0,07 A²s	Optical function display	No
Power output (@ 1.5 In)	0,3 W	Rated breaking capacity	1,5 kA
Version	Fuse accessories	Voltage drop	280 mV

Rating data

Rated voltage	250 V	Rated current	0,25 A
---------------	-------	---------------	--------

Classifications

ETIM 6.0	EC000035	ETIM 7.0	EC000035
ETIM 8.0	EC002704	ETIM 9.0	EC002704
ECLASS 9.0	27-14-20-01	ECLASS 9.1	27-14-20-01
ECLASS 10.0	27-14-20-01	ECLASS 11.0	27-14-20-01
ECLASS 12.0	27-14-20-01	ECLASS 13.0	27-14-20-01
ECLASS 14.0	27-14-20-01		

Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	CAD data – STEP
User Documentation	StorageConditionsTerminalBlocks
Catalogues	Catalogues in PDF-format
Brochures	