



### Principal

Product or Component Type	Disjoncteur
Range	PowerPact P
Current Sensor Rating Range	1000 A
Rated Current	1000 A
Breaking Capacity	65 kAà 240 V AC 35 kA at 480 V AC 18 kAà 600 V AC
AWG Gauge	AWG 3/0...500 kcmil (aluminium / cuivre)
Trip Unit Technology	Électronique, ammeter, Micrologic 6.0 A, LSIG
Product Weight	14,51 kg
Protection Type	Surcharge Court-circuit
Long Time Pick Up Adjustable Range	0,4...1 x Ir

### Complémentaire

Certifications	Listé UL CSA CEI
Rated operational Voltage	600 V AC
Module Type	P-Frame
Mounting Location	Busbar
Mounting Mode	Montage de l'unité
Poles Description	3P
Circuit Breaker Rating Code	G
Electrical Connection	Terminal nut kit ON and OFF end
Continuous Current Rating	80 %
Device Short Name	A
Height	410,46 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Depth	204,47 mm
Width	210,06 mm
Tightening Torque	50 N.m pour 95...240 mm <sup>2</sup> (AWG 3/0...500 kcmil) 1,0...1,3 N.m

## Emballage

Poids de l'emballage (Kg)	14,515 kg
---------------------------	-----------

## Offre de la durabilité

Statut environnemental de l'offre	Produit Green Premium
Régulation REACH	<a href="#">Déclaration REACH</a>
Directive RoHS UE	Conforme <a href="#">Déclaration RoHS UE</a>
Sans mercure	Oui
Information sur les exemptions RoHS	<a href="#">Oui</a>
Régulation RoHS Chine	<a href="#">Déclaration RoHS pour la Chine</a> Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.
Profil environnemental	<a href="#">Profil environnemental du Produit</a>
Profil de circularité	<a href="#">Informations de fin de vie</a>
Sans PVC	Oui