



Principal

Product or Component Type	Disjoncteur
Range	PowerPact P
Current Sensor Rating Range	400 A
Rated Current	400 A
Breaking Capacity	100 kAà 240 V AC 65 kAà 480 V AC 25 kAà 600 V AC
Trip Unit Technology	Électronique, standard, Micrologic 3.0, LI
AWG Gauge	AWG 3/0...500 kcmil (aluminium / cuivre) pour 3 câble(s)

Complémentaire

Device Short Name	A
Certifications	CSA CEI Listé UL
Rated operational Voltage	600 V AC
Module Type	P-Frame
Mounting Location	Bolt-on
Mounting Mode	Montage de l'unité
Poles Description	3P
Circuit Breaker Rating Code	J
Continuous Current Rating	80 %
Electrical Connection	Cosses charge Cosses ligne
Tightening Torque	50 N.m pour 95...240 mm ² (AWG 3/0...500 kcmil) 1,0...1,3 N.m
Height	326,64 mm
Width	210,06 mm
Depth	204,47 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Emballage

Poids de l'emballage (Kg)	14,515 kg
---------------------------	-----------

Offre de la durabilité

Statut environnemental de l'offre	Produit Green Premium
Régulation REACH	Déclaration REACH
Directive RoHS UE	Conforme Déclaration RoHS UE
Sans mercure	Oui
Information sur les exemptions RoHS	Oui
Régulation RoHS Chine	Déclaration RoHS pour la Chine Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.
Profil environnemental	Profil environnemental du Produit
Profil de circularité	Informations de fin de vie
Sans PVC	Oui

Garantie contractuelle

Garantie	18 months
----------	-----------