



Principal

Product	Definite Purpose Starter
Ampere Rating	50 A
Horsepower Rating	3 hpà 115 V AC, monophasé 10 hpà 230 V AC, monophasé 15 hpà 230 V AC, 3 phases 30 hpà 460 V AC, 3 phases 30 hpà 575 V AC, 3 phases
Maximum Voltage Rating	600 V AC
Control Circuit Voltage	110 V AC at 50 Hz 120 V AC at 60 Hz
Phase	3 phases

Complémentaire

Enclosure Material	Feuille d'acier peint
Enclosure Rating	NEMA 1
Locked Rotor Amperes	300 Aà 230 V AC 250 Aà 460 V AC 200 Aà 575 V AC
Number of Poles	3P
Range	DPS
Overload Type	Melting alloy
Number of Thermal Units	3

Emballage

Poids de l'emballage (Kg)	4,323 kg
---------------------------	----------

Offre de la durabilité

Régulation REACH	Déclaration REACH
Directive RoHS UE	Conforme Déclaration RoHS UE
Sans mercure	Oui
Information sur les exemptions RoHS	Oui
Régulation RoHS Chine	Déclaration RoHS pour la Chine Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.

Garantie contractuelle

Garantie	18 months
----------	-----------