



GU10



MR16



MR16
E26



A19



Paquet de 4 A19

Code de commande	Description	Watts (W)	Culot	Volts (VCA)	Temp. de couleur (K)	IRC	Vie L70 (h)	Flux lumineux (lm)	Faisceau (°)	CBCP (cd)	Équivalent traditionnel (W)	Capacité de gradation (Oui/Non)	Qté caisse (int./ext.)
GU10													
66304	GU10/6.5W/27K/40/CHOICE/STD	6.5	GU10	120	2 700	≥80	15 000	500	40	778	50	Oui	1/24
66306	GU10/6.5W/30K/40/CHOICE/STD	6.5	GU10	120	3 000	≥80	15 000	500	40	778	50	Oui	1/24
66308	GU10/6.5W/40K/40/CHOICE/STD	6.5	GU10	120	4 000	≥80	15 000	500	40	778	50	Oui	1/24
MR16													
66309	MR16/12V/6.5W/27K/35/CHOICE/STD	6.5	GU5.3	12	2 700	≥80	25 000	500	35	1 772	50	Oui	1/24
66310	MR16/12V/6.5W/30K/35/CHOICE/STD	6.5	GU5.3	12	3 000	≥80	25 000	500	35	1 772	50	Oui	1/24
66311	MR16/12V/6.5W/40K/35/CHOICE/STD	6.5	GU5.3	12	4 000	≥80	25 000	500	35	1 772	50	Oui	1/24
MR16-E26													
66354	MR16E26/7W/30K/35/CHOICE/STD	7	E26	120	3 000	82	15 000	500	35	1 321	50	Oui	6/48
A19													
66267 ¹	A19/6W/27K/ND/CHOICE/STD	6	E26	120	2 700	≥80	15 000	480	-	-	40	Non	6/48
66268 ¹	A19/6W/30K/ND/CHOICE/STD	6	E26	120	3 000	≥80	15 000	480	-	-	40	Non	6/48
66269 ¹	A19/9.5W/27K/ND/CHOICE/STD	9.5	E26	120	2 700	≥80	15 000	800	-	-	60	Non	6/48
66270 ¹	A19/9.5W/30K/ND/CHOICE/STD	9.5	E26	120	3 000	≥80	15 000	800	-	-	60	Non	6/48
Paquet de 4 A19													
66271 ¹	A19/9.5W/27K/ND/CHOICE/STD 4P	9.5	E26	120	2 700	≥80	15 000	800	-	-	60	Non	1/12
66272 ¹	A19/9.5W/30K/ND/CHOICE/STD 4P	9.5	E26	120	3 000	≥80	15 000	800	-	-	60	Non	1/12
66273 ¹	A19/9.5W/40K/ND/CHOICE/STD 4P	9.5	E26	120	4 000	≥80	15 000	800	-	-	60	Non	1/12
66274 ¹	A19/9.5W/50K/ND/CHOICE/STD 4P	9.5	E26	120	5 000	≥80	15 000	800	-	-	60	Non	1/12

Les valeurs de lumen proviennent des essais photométriques. Pour connaître la liste complète des gradateurs compatibles et des produits homologués Energy Star, veuillez consulter www.standardpro.com

