

CH363RBEI

100A 3P Type3R 600V Heavy Duty Fusible Safety Switch With Electrical Interlock



Principal

Product	Single Throw Safety Switch
Disconnect Type	Fusible disconnect
Number of Poles	3
Electrical Connection	Cosses
Duty Rating	Renforcé

Complémentaire

Line Rated Current	100 A
Factory Installed Neutral	None
Mounting Type	Saillie
Voltage Rating	600 V AC/DC
Wire Size	AWG 12...AWG 1/0 aluminium De AWG 14 à AWG 1/0 cuivre
Puissance moteur hp	25 hp à 480 V AC 50...60 Hz pour 3 phases moteurs conformément à NEC 240.6 60 hp à 480 V AC 50...60 Hz pour 3 phases moteurs conformément à NEC 430.52 30 hp à 600 V AC 50...60 Hz pour 3 phases moteurs conformément à NEC 240.6 75 hp à 600 V AC 50...60 Hz pour 3 phases moteurs conformément à NEC 430.52 20 hp at 250 V DC 50 hp à 600 V DC
Hauteur	539,75 mm
Largeur	260,35 mm
Profondeur	162,05 mm
Couple de serrage	5,65 N.m (AWG 3...AWG 1) 5.08 N.m (AWG 6...AWG 4) 4.52 N.m (AWG 8) 3.95 N.m for 2.06...5.261 mm ² (AWG 14...AWG 10) 3.95 N.m (AWG 14...AWG 10)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environnement

Certifications	CSA
Enclosure Rating	NEMA 3R galvanized steel

Emballage

Poids de l'emballage (Kg)	4,536 g
---------------------------	---------
