



### Principal

Product or Component Type	Disjoncteur
Range	PowerPact P
Current Sensor Rating Range	400 A
Rated Current	400 A
Breaking Capacity	100 kA à 240 V AC 65 kA à 480 V AC 25 kA à 600 V AC
AWG Gauge	AWG 3/0...500 kcmil (aluminium / cuivre) pour 3 câble(s)
Trip Unit Technology	Électronique, harmonique, Micrologic 6.0 H, LSIG

### Complémentaire

Certifications	CEI CSA Listé UL
Rated operational Voltage	600 V AC
Module Type	P-Frame
Mounting Location	Busbar
Mounting Mode	I-Line
Poles Description	3P
Circuit Breaker Rating Code	J
Electrical Connection	I-Line connection ligne Cosses charge
Continuous Current Rating	80 %
Device Short Name	A
Communication Interface	Modbus
Height	326,64 mm
Depth	204,47 mm
Width	210,06 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Tightening Torque	50 N.m pour 95...240 mm <sup>2</sup> (AWG 3/0...500 kcmil) 1,0...1,3 N.m
-------------------	---

## Emballage

Poids de l'emballage (Kg)	14,515 kg
---------------------------	-----------

## Offre de la durabilité

Statut environnemental de l'offre	Produit Green Premium
Régulation REACH	<a href="#">Déclaration REACH</a>
Directive RoHS UE	Conforme <a href="#">Déclaration RoHS UE</a>
Sans mercure	Oui
Information sur les exemptions RoHS	Oui
Régulation RoHS Chine	<a href="#">Déclaration RoHS pour la Chine</a> Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.
Profil environnemental	<a href="#">Profil environnemental du Produit</a>
Profil de circularité	<a href="#">Informations de fin de vie</a>
Sans PVC	Oui

## Garantie contractuelle

Garantie	18 months
----------	-----------