

**STARTERKIT WCU 650**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

www.weidmueller.com



With the fully encapsulated WCU 501 and WCU 650 logic modules, you monitor, control and regulate your processes - even under extreme environmental conditions. In this regard, the WCU series offers optimum dimensions, performance, robustness and user-friendliness. The graphic and intuitive Micon-L programming environment enables flexible switching of the analogue and digital inputs, plus the digital outputs too. The scope of both the software and the hardware can be expanded to suit customer requirements upon request. .

**General ordering data**

Version	graphically programmable logic module incl. programming adapter, CAN interface, Mounting foot
Order No.	<a href="#">2007290000</a>
Type	STARTERKIT WCU 650
GTIN (EAN)	4050118392517
Qty.	1 pièce(s)
Delivery status	<b>This article will no longer be available in the future.</b>
Available until	2024-06-30
Alternative product	<a href="#">2753440000</a>

**STARTERKIT WCU 650****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Caractéristiques techniques****Dimensions and weights**

Depth	30 mm	Depth (inches)	1,181 inch
Height	93 mm	Height (inches)	3,661 inch
Width	45 mm	Width (inches)	1,772 inch
Net weight	178 g		

**Temperatures**

Storage temperature	-40 °C...70 °C	Operating temperature	-40 °C...70 °C
Humidity	5 - 95% rel. humidity		

**Connection data**

Type of connection	Plug-in spring-type terminals (0.25 - 1.5 mm <sup>2</sup> )
--------------------	---

**General data**

Vibration resistance	min. 50 m/s <sup>2</sup> (5 g) @ 10...150 Hz
----------------------	--

**Power supply**

Reverse polarity protection	yes (combined with external fuse)
-----------------------------	-----------------------------------

**System data**

Interface	TTL 232
-----------	---------

**Classifications**

ETIM 6.0	EC001417	ETIM 7.0	EC001417
ETIM 8.0	EC001417	ETIM 9.0	EC001417
ECLASS 9.0	27-24-22-16	ECLASS 9.1	27-24-22-16
ECLASS 10.0	27-24-22-16	ECLASS 11.0	27-24-22-16
ECLASS 12.0	27-24-22-16	ECLASS 13.0	27-24-22-16
ECLASS 14.0	27-24-22-16		

**Environmental Product Compliance**

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%

**Approvals**

Approvals



ROHS	Conform
UL File Number Search	UL Website
Certificate no. (cULus)	E141197

Date de création 26 novembre 2024 13:23:56 CET

Niveau du catalogue 26.11.2024 / Toutes modifications techniques réservées

**STARTERKIT WCU 650**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Caractéristiques techniques****Downloads**

Engineering Data	<a href="#">CAD data – STEP</a>
Software	<a href="#">Runtime Software – Programmiersoftware miCon-L</a>
User Documentation	<a href="#">Handbuch WCU-Serie Deutsch</a> <a href="#">Manual WCU-Series English</a>
Catalogues	<a href="#">Catalogues in PDF-format</a>

**Fiche de données**

**STARTERKIT WCU 650**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Dessins**

