



## Principal

Product	Combination Starter
Type	S
Control Circuit Type	Separate control circuit

## Complémentaire

Control Circuit Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Starter Type	Non réversible
Number of Poles	3P
Horsepower Rating	10 hpà 230 V AC, 3 phases 25 hpà 575 V AC, 3 phases 7,5...10 hpà 200 V AC, 3 phases 20...25 hpà 460 V AC, 3 phases
Maximum Voltage Rating	600 V AC
Control Units	No control units
Pilot Light	Sans signalisation
Auxiliary Contacts	Sans
Type de surcharge thermique	Melting alloy 3
Disconnect Type	Mag-Gard circuit breaker

## Environnement

Enclosure Type	NEMA 12 feuille d'acier peint et with external reset
Taille NEMA	2

## Emballage

Poids de l'emballage (Kg)	19,477 kg
---------------------------	-----------

## Offre de la durabilité

Directive RoHS UE	Non conforme
Régulation RoHS Chine	<a href="#">Déclaration RoHS pour la Chine</a> Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.

## Garantie contractuelle

Garantie	18 months
----------	-----------