



Principal

Product or Component Type	Disjoncteur
Range	PowerPact P
Current Sensor Rating Range	800 A
Rated Current	800 A
Breaking Capacity	65 kAà 240 V AC 50 kAà 480/600 V AC
AWG Gauge	AWG 3/0...500 kcmil (aluminium / cuivre) pour 3 câble(s)
Trip Unit Technology	Électronique, ammeter, Micrologic 5.0 A, LSI
Protection Type	Court-circuit Surcharge
Long Time Pick Up Adjustable Range	0,4...1 x Ir

Complémentaire

Certifications	CSA CEI Listé UL
Rated operational Voltage	600 V AC
Module Type	P-Frame
Mounting Location	Busbar
Mounting Mode	Montage de l'unité
Poles Description	3P
Circuit Breaker Rating Code	K
Electrical Connection	Terminal nut kit ON and OFF end
Continuous Current Rating	100 %
Device Short Name	A
Height	326,64 mm
Depth	204,47 mm
Width	210,06 mm
Tightening Torque	50 N.m pour 95...240 mm ² (AWG 3/0...500 kcmil)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Emballage

Poids de l'emballage (Kg)	14,515 kg
---------------------------	-----------

Offre de la durabilité

Statut environnemental de l'offre	Produit Green Premium
Régulation REACH	Déclaration REACH
Directive RoHS UE	Conforme Déclaration RoHS UE
Sans mercure	Oui
Information sur les exemptions RoHS	Oui
Régulation RoHS Chine	Déclaration RoHS pour la Chine Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.
Profil environnemental	Profil environnemental du Produit
Profil de circularité	Informations de fin de vie
Sans PVC	Oui