



Principal

Product	Surge protection device
Range	Surgelogic
Device Short Name	IMA

Complémentaire

Surge Current	120 kA par phase
Voltage Rating	480Y/277 V AC
Number of Phases	3 phases
Wiring Configuration	4 fils
Connection	Cosses AWG 12...AWG 2 aluminium / cuivre 4 N.m
MCOV	320 V
Nominal Discharge Current	20 kA
SCCR	200 kA
Provided Equipment	Alarm enable/disable switch Diagnostic display Backplane Câbles
Height	155,7 mm
Width	250,4 mm
Depth	92,7 mm

Environnement

Enclosure Rating	NEMA 2
Standards	UL 1449:ed. 4 CSA C22.2 No 8:1986 UL 96A:ed. 12 UL 1283 IEC 61643-1

Emballage

Poids de l'emballage (Kg)	3,810 kg
---------------------------	----------

Offre de la durabilité

Régulation REACH	Déclaration REACH
Directive RoHS UE	Conforme Déclaration RoHS UE
Sans mercure	Oui
Information sur les exemptions RoHS	Oui
Régulation RoHS Chine	Déclaration RoHS pour la Chine Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.