

2510KGJ2

Switch, manual, 30A, 3 pole, 10 HP at 575 VAC,
three phase, toggle operated, no indicator, NEMA
1 jumbo enclosure



Principal

Product	Single Unit Manual Switch
Type	K

Complémentaire

Current Rating	30 A
Cable Entry	0.5" and 0.75" knock-outs (top and bottom)
Horsepower Rating	2 hpà 115 V AC 1 hpà 90 V DC 2 hpà 115 V DC 1,5 hpà 230 V DC 7,5 hpà 230 V AC 10 hpà 460 V AC 10 hpà 575 V AC
Maximum Voltage Rating	600 V AC 230 V DC
Number of Poles	3P
Control Unit Type	Par maneton
Number of Phases	3 phases
Pilot Light	Sans signalisation
Starter Type	Non réversible
Electrical Connection	Borniers à vis-étrier
Wire Gauge	AWG 14...AWG 10 cuivre
Hauteur	107,95 mm
Largeur	73,15 mm
Profondeur	69,85 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Environnement

Certifications	UL listed file E42243 CCN NLRV CSA LR25490 class 3211 05
NEMA Enclosure Rating	NEMA 1 feuille d'acier peint oversized

Emballage

Poids de l'emballage (Kg)	530,703 g
Hauteur de l'emballage 1	9,652 cm
Largeur de l'emballage 1	7,874 cm
Longueur de l'emballage 1	12,446 cm

Offre de la durabilité

Régulation REACH	Déclaration REACH
Sans SVHC REACH	Oui
Directive RoHS UE	Non conforme
Régulation RoHS Chine	Déclaration RoHS pour la Chine Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.
Sans PVC	Oui

Garantie contractuelle

Garantie	18 months
----------	-----------