

## H0,75/14 W BD GSP

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)



- Linked wire-end ferrules on reel (5,000 pcs.)
- Weidmüller colour code
- DIN colour code
- other colour code

### General ordering data

|            |  |
|------------|--|
| Version    | Wire-end ferrule, Standard, 10 mm, 8 mm, white |
| Order No.  | <a href="#">9005820000</a>                     |
| Type       | H0,75/14 W BD GSP                              |
| GTIN (EAN) | 4008 1902 75884                                |
| Qty.       | 5 000 pièce(s)                                 |
| Packaging  | Reel   |

## H0,75/14 W BD GSP

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

www.weidmueller.com

## Caractéristiques techniques

### Dimensions and weights

Net weight 0,12 g

### Technical data

|                        |                                  |         |          |
|------------------------|----------------------------------|---------|----------|
| Description of article | Wire end ferrules on reel, white | Version | Standard |
|------------------------|----------------------------------|---------|----------|

### Wire-end ferrules

|                             |                      |   |             |
|-----------------------------|----------------------|---|-------------|
| Collar diameter (D2)        | 2,8 mm               | Colour code                             | Weidmueller |
| Conductor cross-section     | 0,75 mm <sup>2</sup> | Contact surface diameter (D1)           | 1,2 mm      |
| Contact surface length (L2) | 8 mm                 | L1 in mm                                | 14 mm       |
| Metal sleeve thickness (S1) | 0,15 mm              | Plastic collar thickness (S2)           | 0,25 mm     |
| Stripping length            | 10 mm                | Wire connection cross section AWG, max. | AWG 18      |

### Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000005    | ETIM 7.0    | EC000005    |
| ETIM 8.0    | EC000005    | ETIM 9.0    | EC000005    |
| ECLASS 9.0  | 27-40-02-01 | ECLASS 9.1  | 27-40-02-01 |
| ECLASS 10.0 | 27-40-02-01 | ECLASS 11.0 | 27-40-02-01 |
| ECLASS 12.0 | 27-40-02-01 | ECLASS 13.0 | 27-40-02-01 |
| ECLASS 14.0 | 27-40-02-01 |             |             |

### Environmental Product Compliance

|                        |                             |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC             | No SVHC above 0.1 wt%       |

### Approvals

Approvals



|                         |            |
|-------------------------|------------|
| ROHS                    | Conform    |
| UL File Number Search   | UL Website |
| Certificate no. (cULus) | E499744    |

### Downloads

|                    |  |
|--------------------|--|
| Engineering Data   | <a href="#">CAD data – STEP</a>  |
| User Documentation | <a href="#">Technical information - EN</a><br><a href="#">Technical information - DE</a> |
| Catalogues         | <a href="#">Catalogues in PDF-format</a>   |
| Brochures          |  |

**Fiche de données**

**H0,75/14 W BD GSP**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Dessins**

**Drawing**

