

Douilles fluorescentes


0.51" - 12.95 mm



38033

1.02" - 25.91 mm

1.31" - 33.27 mm



38034

1.25" - 31.75 mm

1.43" - 36.32 mm



10736

2.33" - 59.18 mm

1.43" - 36.32 mm



10737

2.75" - 69.85 mm

1.26" - 32.00 mm



38017

2.00" - 50.80 mm

0.33" - 8.38 mm



38197

1.96" - 49.78 mm

1.01" - 25.65 mm



38240

1.65" - 41.91 mm

1.27" - 32.26 mm



38241

1.66" - 42.16 mm

1.26" - 32.00 mm



38242

2.00" - 50.80 mm

1.27" - 32.26 mm



38243

1.60" - 40.64 mm

0.72" - 18.29 mm



38244

1.59" - 40.39 mm

1.22" - 31.00 mm



58791

1.66" - 42.16 mm

1.22" - 31.00 mm



58792

1.50" - 38.10 mm

1.07" - 27.18 mm



38003

0.57" - 14.48 mm

Code de commande	Description	Culot	Volts (V)	Watts (W)	Qté caisse (int./ext.)
38033	SK1062 CIRCLINE SOCKET/9" LEA	G10-q	600	660	10/2 000
38034	7-9 WT VERTICAL MOUNT	G23 / G23-2	600	75	250/2 500
10736	T8/T12 TALL PRF TURN SCREW MNT	G13	600	660	10/200
10737	T8/T12 W/STARTER Culot SCR MNT	G13	600	660	1/50
38017	T8/T12 TALL PRF w/CN SCR/SLDE	G13	600	660	10/300
38197	T8/T12 TALL PRF SNAP-IN SHUNTED	G13	600	660	250/2 500
38240	T8/T12 LOW PRF SLIDE MNT STD	G13	600	660	10/1 000
38241	T8/T12 LOW PRF SLIDE MNT SHUNTED STD	G13	600	660	10/1 000
38242	T8/T12 TALL PRF SLIDE MNT STD	G13	600	660	10/1 000
38243	T8/T12 LOW PRF U SLIDE MNT STD	G13	600	660	1/10
38244	T8/T12 LOW PROFILE U SLIDE MOUNT SHT STD	G13	600	660	10/1 000
58791	T8/T12 ROTARY SHUNTED TALL LOCKABLE	G13	600	660	10/500
58792	T8/T12 ROTARY SHUNTED LOW LOCKABLE	G13	600	660	10/500
38003	T5 REAR SNP MNT LOCK w/SPG PLT	G5	600	75	10/2 000

