

Fiche Produit

Caractéristiques

2510KR2

Switch, manual, 30A, 3 pole, 10 HP at 575 VAC, three phase, toggle operated, no indicator, NEMA 7/9, one conduit opening



Principal

Product	Single Unit Manual Switch
Type	K

Complémentaire

Current Rating	20 A
Cable Entry	0.75 NPT (bottom)
Horsepower Rating	2 hpà 115 V AC 1 hpà 90 V DC 2 hpà 115 V DC 1,5 hpà 230 V DC 7,5 hpà 230 V AC 10 hpà 460 V AC 10 hpà 575 V AC
Maximum Voltage Rating	600 V AC 230 V DC
Number of Poles	3P
Control Unit Type	Par maneton
Number of Phases	3 phases
Pilot Light	Sans signalisation
Starter Type	Non réversible
Electrical Connection	Borniers à vis-étrier
Wire Gauge	AWG 14...AWG 10 cuivre
Hauteur	161,54 mm
Largeur	100,33 mm
Profondeur	110,49 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environnement

Certifications	UL listed file E58760 CCN NPXZ CSA LR26817 class 3218 04
NEMA Enclosure Rating	NEMA 3R/7/9 cast aluminium standard size

Emballage

Poids de l'emballage (Kg)	1,610 kg
Hauteur de l'emballage 1	11,684 cm
Largeur de l'emballage 1	13,970 cm
Longueur de l'emballage 1	17,780 cm

Offre de la durabilité

Régulation REACH	Déclaration REACH
Sans SVHC REACH	Oui
Directive RoHS UE	Non conforme
Régulation RoHS Chine	Déclaration RoHS pour la Chine Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.
Sans PVC	Oui

Garantie contractuelle

Garantie	18 months
----------	-----------