

Conduit rigide en PVC

Liste de prix au Canada
Liste de prix : E-RCP-PLV22-F
En vigueur : 3 mars 2025
Remplace : 9 février 2024
Nos prix n'incluent pas les taxes

Dim mm (po)	No. du Produit		No. de UPC		Pieds Par	Pieds Par	Poids Lbs. Par C Pi	Prix par 100
	10 Pd	20 Pd	10 Pd	20 Pd	Ballot 10 Pd	Ballot 20 Pd		
Conduit rigide en PVC								
12 (½)	RC4000510	RC4000520	15500	15510	6,000	12,000	16	\$563.00
19 (¾)	RC4000710	RC4000720	15520	15530	4,400	8,800	22	\$703.00
25 (1)	RC4001010	RC4001020	15540	15550	3,600	7,200	32	\$1,052.00
32 (1¼)	RC4001210	RC4001220	15560	15570	3,300	6,600	44	\$1,318.00
38 (1½)	RC4001510	RC4001520	15580	15590	2,250	4,500	52	\$1,765.00
50 (2)	RC4002010	RC4002020	15600	15610	1,400	2,800	71	\$2,203.00
63 (2½)	RC4002510	RC4002520	15620	15630	780	1,560	113	\$3,811.00
75 (3)	RC4003010	RC4003020	15640	15650	780	1,560	148	\$5,006.00
90 (3½)	RC4003510	RC4003520	15660	15665	630	1,260	178	\$6,283.00
100 (4)	RC4004010	RC4004020	15670	15680	600	1,200	200	\$7,073.00
125 (5)	RC4005010	RC4005020	15690	15700	230	460	286	\$10,066.00
150 (6)	RC4006010	RC4006020	15710	15715	260	520	371	\$13,380.00
200 (8)	RC4008010	RC4008020	20438	20439	140	280	559	\$21,111.00

Remarque : Longueurs de 20 pieds disponibles aux prix ci-haut mentionnés. Chaque longueur de tuyaux possède un bout évasé (cloche intégrée).

Dim mm (po)	Pièces Par Ballot	Ballot Par C.C.		Pieds Par C.C.	Poids Par C.C.
		10 Pd	20 Pd		
12 (½)	600	40	20	240,000	38,400
19 (¾)	440	48	24	211,200	46,464
25 (1)	360	36	18	129,600	41,280
32 (1¼)	330	32	16	105,600	46,464
38 (1½)	225	40	20	90,000	37,440
50 (2)	140	40	20	56,000	39,760
63 (2½)	78	40	20	31,200	44,748
75 (3)	78	32	16	24,960	41,677
90 (3½)	63	32	16	20,160	35,885
100 (4)	60	32	16	19,200	38,486
125 (5)	23	32	16	7,360	30,096
150 (6)	26	32	16	8,320	30,867
200 (8)	10	32	16	3,200	18,958

Nombre moyen de joints par cannette				
Dim mm (po)	½ Chopine (250mL)	Chopine (500mL)	Pinte (1/L)	Gallon (4/L)
50 (2)	17	17	20	240,000
75 (3)	15	15	24	211,200
90 (3½)	13	13	18	129,600
100 (4)	10	10	16	105,600
125 (5)	8	8	20	90,000
150 (6)	5	5	20	56,000

Normes et certifications

 C22.2 No. 211.2

 UL 651

FT-4 Approuvé ½" - 6"