

WSD 2.5/SCAN WTR2.5**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Product image

The component plug is used to integrate an electrical component in a disconnect terminal block. After soldering the electronic component, the plug can be integrated into the disconnection area of our disconnect terminal blocks and thus changes the disconnect terminal block into a modular terminal block with integrated electronic component.

General ordering data

Version	Component plug (terminal), Plug-in connection, Plugged, dark beige
Order No.	1058760000
Type	WSD 2.5/SCAN WTR2.5
GTIN (EAN)	4008 190028398
Qty.	25 pièce(s)

WSD 2.5/SCAN WTR2.5**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Caractéristiques techniques**Dimensions and weights**

Depth	29,58 mm	Depth (inches)	1,165 inch
Height	38,4 mm	Height (inches)	1,512 inch
Width	5 mm	Width (inches)	0,197 inch
Net weight	3,68 g		

Temperatures

Storage temperature	-25 °C...55 °C	Continuous operating temp., min.	-50 °C
Continuous operating temp., max.	120 °C		

Material data

Material	Wemid	Colour	dark beige
UL 94 flammability rating	V-0		

System specifications

Version	Diode module	End cover plate required	No
Number of levels	1	PE connection	No

Additional technical data

Explosion-tested version	No	Type of fixing	Plugged
Type of mounting	Plugged		

CSA rating data

Certificate No. (CSA)	154685-1152890
-----------------------	----------------

Conductors for clamping (rated connection)

Connection direction	top	Type of connection	Plug-in connection
----------------------	-----	--------------------	--------------------

UL rating data

Certificate No. (UR)	E60693
----------------------	--------

Classifications

ETIM 6.0	EC002018	ETIM 7.0	EC002018
ETIM 8.0	EC002018	ETIM 9.0	EC002018
ECLASS 9.0	27-14-11-49	ECLASS 9.1	27-14-11-49
ECLASS 10.0	27-14-11-49	ECLASS 11.0	27-14-11-49
ECLASS 12.0	27-14-11-49	ECLASS 13.0	27-25-03-05
ECLASS 14.0	27-25-03-05		

Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%

Fiche de données**WSD 2.5/SCAN WTR2.5**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Caractéristiques techniques**Approvals**

Approvals



ROHS	Conform
UL File Number Search	UL Website
Certificate No. (UR)	E60693

Downloads

Engineering Data	CAD data – STEP
User Documentation	StorageConditionsTerminalBlocks
Catalogues	Catalogues in PDF-format