



Des produits de qualité. L'excellence du service.

Unité de distribution de l'alimentation de base pour montage sur bâti

Série 1583

15A | 125V monophasé | Prises 5-15R accessibles à l'avant ou à l'arrière

Caractéristiques



- Conçue pour la distribution de l'alimentation depuis l'avant ou l'arrière de la barre.
- Pour montage horizontal sur bâti de 19 po de 1 U.
- Disponible avec interrupteur marche-arrêt éclairé ou voyant rouge indiquant que la barre est sous tension.
- Les modèles à 6 prises comprennent 2 prises avec espace supplémentaire pour le branchement de la plupart des transformateurs enfichables.
- Revêtement en poudre gris ou noir ASA 61.
- [Cliquez ici pour voir notre modèle protégé contre les surtensions.](#)

Spécifications

- Cordon d'alimentation de calibre 14 de service robuste de type 14/3 SJT convenant à des plages de températures extrêmes et fiche moulée intégrée.
- Les types de fiches disponibles sont les fiches à lame droite NEMA 5-15P et les fiches à verrouillage NEMA L5-15P.
- Comprend un disjoncteur de 15 A, 125 V c. a. pour prévenir une surcharge accidentelle.
- Homologuée UL/cUL, norme UL1363, fichier no E166039 et CSA C22.2 no 308-14 et CSA C22.2 no 0.4-04



Galerie



Accessoires

- Quincaillerie d'assemblage
- Ensemble d'adaptateurs de profondeur pour rails

Black Finish

Illuminated On/Off Switch Part No.	Illuminated Light Only Part No.	Overall Dimensions			Number of Outlets		NEMA Type		Plug		Cord Length	Rack Units
		Height	Width	Depth	Front	Rear	Outlet	Plug	Blade Type	Rotated Outlets		
1583H12A1BKX	1583T12A1BKX	1.72	19.00	2.66	6	6	5-15R	5-15P	Straight	No	6 ft	1U
1583H12A1BKXRA	1583T12A1BKXRA	1.72	19.00	2.66	6	6	5-15R	5-15P	Straight	Yes	6 ft	1U

Illuminated On/Off Switch Part No.	Illuminated Light Only Part No.	Overall Dimensions			Number of Outlets		NEMA Type		Plug Blade Type	Rotated Outlets	Cord Length	Rack Units
		Height	Width	Depth	Front	Rear	Outlet	Plug				
1583H12B1BKX	1583T12B1BKX	1.72	19.00	2.66	6	6	5-15R	5-15P	Straight	No	15 ft	1U
1583H12B1BKXRA	1583T12B1BKXRA	1.72	19.00	2.66	6	6	5-15R	5-15P	Straight	Yes	15 ft	1U
1583H12C1BKX	1583T12C1BKX	1.72	19.00	2.66	6	6	5-15R	L5-15P	Locking	No	6 ft	1U
1583H12D1BKX	1583T12D1BKX	1.72	19.00	2.66	6	6	5-15R	L5-15P	Locking	No	15 ft	1U
1583H6A1BK	1583T6A1BK	1.72	19.00	2.66	0	6	5-15R	5-15P	Straight	No	6 ft	1U
1583H6A1BKRA	1583T6A1BKRA	1.72	19.00	2.66	0	6	5-15R	5-15P	Straight	Yes	6 ft	1U
1583H6A1BKX	1583T6A1BKX	1.72	19.00	2.66	2	4	5-15R	5-15P	Straight	No	6 ft	1U
1583H6B1BK	1583T6B1BK	1.72	19.00	2.66	0	6	5-15R	5-15P	Straight	No	15 ft	1U
1583H6B1BKRA	1583T6B1BKRA	1.72	19.00	2.66	0	6	5-15R	5-15P	Straight	Yes	15 ft	1U
1583H6B1BKX	1583T6B1BKX	1.72	19.00	2.66	2	4	5-15R	5-15P	Straight	No	15 ft	1U
1583H6C1BK	1583T6C1BK	1.72	19.00	2.66	0	6	5-15R	L5-15P	Locking	No	6 ft	1U
1583H6C1BKRA	1583T6C1BKRA	1.72	19.00	2.66	0	6	5-15R	L5-15P	Locking	Yes	6 ft	1U
1583H6C1BKX	1583T6C1BKX	1.72	19.00	2.66	2	4	5-15R	L5-15P	Locking	No	6 ft	1U
1583H6D1BK	1583T6D1BK	1.72	19.00	2.66	0	6	5-15R	L5-15P	Locking	No	15 ft	1U
1583H6D1BKRA	1583T6D1BKRA	1.72	19.00	2.66	0	6	5-15R	L5-15P	Locking	Yes	15 ft	1U
1583H6D1BKX	1583T6D1BKX	1.72	19.00	2.66	2	4	5-15R	L5-15P	Locking	No	15 ft	1U
1583H8A1BK	1583T8A1BK	1.72	19.00	2.66	0	8	5-15R	5-15P	Straight	No	6 ft	1U
1583H8B1BK	1583T8B1BK	1.72	19.00	2.66	0	8	5-15R	5-15P	Straight	No	15 ft	1U
1583H8C1BK	1583T8C1BK	1.72	19.00	2.66	0	8	5-15R	L5-15P	Locking	No	6 ft	1U
1583H8D1BK	1583T8D1BK	1.72	19.00	2.66	0	8	5-15R	L5-15P	Locking	No	15 ft	1U

ASA 61 Grey Finish

Illuminated On/Off Switch Part No.	Illuminated Light Only Part No.	Overall Dimensions			Number of Outlets		Outlet NEMA Type	Rotated Outlets	Cord Length	Plug Blade Type	NEMA Plug Type	Rack Units
		Height	Width	Depth	Front	Rear						
1583H6A1	1583T6A1	1.72	19.00	2.66	0	6	5-15R	No	6 ft	Straight	5-15P	1U
1583H6B1	1583T6B1	1.72	19.00	2.66	0	6	5-15R	No	15 ft	Straight	5-15P	1U
1583H6C1	1583T6C1	1.72	19.00	2.66	0	6	5-15R	No	6 ft	Locking	L5-15P	1U
1583H6D1	1583T6D1	1.72	19.00	2.66	0	6	5-15R	No	15 ft	Locking	L5-15P	1U
1583H8A1	1583T8A1	1.72	19.00	2.66	0	8	5-15R	No	6 ft	Straight	5-15P	1U
1583H8B1	1583T8B1	1.72	19.00	2.66	0	8	5-15R	No	15 ft	Straight	5-15P	1U
1583H8C1	1583T8C1	1.72	19.00	2.66	0	8	5-15R	No	6 ft	Locking	L5-15P	1U
1583H8D1	1583T8D1	1.72	19.00	2.66	0	8	5-15R	No	15 ft	Locking	L5-15P	1U

Les données sont sujettes à changement sans préavis

© 2021. Hammond Manufacturing Ltd. Tous droits réservés.