

8702SCO8V02S

NEMA Contactor, Type S, reversing, horizontal, Size 1, 27A, 10 HP at 575 VAC, 3 phase, up to 100 kA, 3 pole, 120 VAC coil, open style



Principal

Product Type	Contacteur
Product Range	Type S
Contacteur Type	Réversible

Complémentaire

NEMA Size	1
Rated Current	27 A
Number of Poles	3P
Mounting Orientation	Horizontale
Wiring Mode	3 fils
Maximum Voltage Rating	600 V AC
Phase	3 phases
Horsepower Rating	7.5 HP at 200 V AC 7.5 HP at 230 V AC 10 HP at 460 V AC 10 HP at 575 V AC
SCCR	Disjoncteur 70 A maximum, SCCR: 100 kA at 480 V AC Fusible J 60 A maximum, SCCR: 100 kA at 600 V AC Fusible T 60 A maximum, SCCR: 100 kA at 600 V AC Fusible RK1 60 A maximum, SCCR: 100 kA at 600 V AC Fusible RK5 60 A maximum, SCCR: 100 kA at 600 V AC
Coil Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Control Circuit Type	Separate control circuit
Control Units	No control units
Pilot Light	Sans signalisation
Other Equipment	Fusible non fourni

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Terminal Type	Borniers à vis-étrier
Height	127,00 mm
Width	181,10 mm
Depth	134,87 mm

Environnement

Enclosure Type	Not rated (open device)
Certifications	Listé UL CSA

Emballage

Poids de l'emballage (Kg)	3,983 kg
Hauteur de l'emballage 1	21,336 cm
Largeur de l'emballage 1	21,336 cm
Longueur de l'emballage 1	30,988 cm

Offre de la durabilité

Directive RoHS UE	Non conforme
Régulation RoHS Chine	Déclaration RoHS pour la Chine Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.

Garantie contractuelle

Garantie	18 months
----------	-----------