


**RS 32 24VDC LD LP 2U****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Product image****General ordering data**

Version	RS-SERIES, Relay module, Number of contacts: 2, CO contact AgNi 90/10, Rated control voltage: 24 V DC $\pm 10\%$ , Continuous current: 4 A, Screw connection, Test button available: No
Order No.	<a href="#">9406121001</a>
Type	RS 32 24VDC LD LP 2U
GTIN (EAN)	4008190027193
Qty.	10 pièce(s)
Delivery status	<b>This article will no longer be available in the future.</b>
Available until	2023-08-31
Alternative product	<a href="#">2773960000</a>

Date de création 26 novembre 2024 13:34:54 CET

Niveau du catalogue 26.11.2024 / Toutes modifications techniques réservées

## RS 32 24VDC LD LP 2U

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Caractéristiques techniques

### Dimensions and weights

Depth	63,5 mm	Depth (inches)	2,5 inch
Height	70 mm	Height (inches)	2,756 inch
Width	25 mm	Width (inches)	0,984 inch
Net weight	44,88 g		

### Temperatures

Storage temperature	-40 °C...60 °C	Operating temperature	-25 °C...40
Humidity	40 °C / 93 % rel. humidity, no condensation		

### Control side

Rated control voltage	24 V DC $\pm$ 10 %	Rated current DC	25 mA
Power rating	0.6 W	Status indicator	red LED
Protective circuit	Free-wheeling diode, Re- verse polarity protection		

### Load side

Rated switching voltage	250 V AC	Max. switching frequency at rated load	0,1 Hz
Max. switching voltage, AC	250 V	Inrush current	6 A
AC switching capacity (resistive), max.	1000 VA	Switch-on delay	< 13 ms
Switch-off delay	$\leq$ 10 ms	Contact type	2 CO contact (AgNi 90/10)
Mechanical service life	30 x 10 <sup>6</sup> switching cycles	Min. switching power	1 mA @ 24 V, 10 mA @ 10 V, 100 mA / 5 V DC

### General data

Version	soldered relay	Rail	TS 32, TS 35
Test button available	No	Mechanical switch position indicator	No
Colour	orange		

### Insulation coordination

Rated voltage	300 V	Pollution severity	2
Surge voltage category	III	Creepage and clearance distance input - output	> 3 mm
Dielectric strength to mounting rail	4 kV <sub>eff</sub> / 1 Min.	Impulse withstand voltage	4 kV (1.2/50 $\mu$ s)
Protection degree	IP20		

### Connection data

Wire connection method	Screw connection	Stripping length, rated connection	8 mm
Clamping range, rated connection	2,5 mm <sup>2</sup>	Clamping range, min.	0,5 mm <sup>2</sup>
Clamping range, max.	4 mm <sup>2</sup>		

## RS 32 24VDC LD LP 2U

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany

www.weidmueller.com

## Caractéristiques techniques

### Classifications

ETIM 6.0	EC001437	ETIM 7.0	EC001437
ETIM 8.0	EC001437	ETIM 9.0	EC001437
ECLASS 9.0	27-37-16-01	ECLASS 9.1	27-37-16-01
ECLASS 10.0	27-37-16-01	ECLASS 11.0	27-37-16-01
ECLASS 12.0	27-37-16-01	ECLASS 13.0	27-37-16-01
ECLASS 14.0	27-37-16-01		

### Environmental Product Compliance

RoHS Compliance Status	Compliant with exemption
RoHS Exemption (if applicable/known)	7a
REACH SVHC	Lead 7439-92-1
SCIP	7b5ffb72-271d-4c73-8b09-bd0aeee3697a

### Approvals

Approvals



ROHS	Conform
------	---------

### Downloads

Approval/Certificate/Document of Conformity	<a href="#">DE_PA_5600_160311_001.pdf</a>
Catalogues	<a href="#">Catalogues in PDF-format</a>

**Fiche de données**

**RS 32 24VDC LD LP 2U**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Dessins**

**Wiring diagram**

