



Principal

Product	Single Throw Safety Switch
Current Rating	60 A
Number of Poles	3
Voltage Rating	600 V AC/DC
Wire Size	AWG 14...AWG 3 cuivre AWG 12...AWG 3 aluminium
Disconnect Type	Fusible disconnect
Short Circuit Current Rating	10 kA H or K 200 kA R, J or L
Mounting Type	Saillie
Factory Installed Neutral	None
Electrical Connection	Cosses
Duty Rating	Renforcé
Certifications	UL listed file E2875
Enclosure Rating	NEMA 4X fiberglass reinforced polyester

Complémentaire

Puissance moteur hp	15 hp at 480 V AC 50...60 Hz for 3 phases motors conforming to NEC 240.6 30 hp at 480 V AC 50...60 Hz for 3 phases motors conforming to NEC 430.52 15 hp at 600 V AC 50...60 Hz for 3 phases motors conforming to NEC 240.6 50 hp at 600 V AC 50...60 Hz for 3 phases motors conforming to NEC 430.52 30 hp at 600 V DC
Largeur	279,40 mm
Hauteur	419,10 mm
Profondeur	223,52 mm
Couple de serrage	5,65 N.m (AWG 3) 5,08 N.m (AWG 6...AWG 4) 4,52 N.m pour 8,367 mm ² (AWG 8)

Emballage

Poids de l'emballage (Kg)	9,652 kg
Hauteur de l'emballage 1	16,500 cm
Largeur de l'emballage 1	8,801 cm
Longueur de l'emballage 1	11,001 cm

Offre de la durabilité

Statut environnemental de l'offre	Produit Green Premium
Régulation REACH	Déclaration REACH
Sans SVHC REACH	Oui
Directive RoHS UE	Conforme Déclaration RoHS UE
Sans mercure	Oui
Information sur les exemptions RoHS	Oui
Régulation RoHS Chine	Déclaration RoHS pour la Chine Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.
Profil environnemental	Profil environnemental du Produit
Sans PVC	Oui

Garantie contractuelle

Garantie	18 months
----------	-----------