

Product data sheet

Specifications



Operator control unit, TeSys Tera,
140 mA, RJ45 connection, flush-
mounted, backlit LCD

LTMTCUF

Product availability: Stock - Normally stocked in distribution facility

Main

Range	TeSys
Product or Component Type	Operator control unit
Display Type	Backlit LCD
Local signalling	4 LEDs

Complementary

Supply	Via the controller
Maximum supply current	140 mA
Standards	CUL EN/IEC 61131-2 UL
Mounting Mode	Flush-mounted
Width	4.6 in (117 mm)
Height	2.8 in (70 mm)
Depth	2.0 in (50 mm)
Net Weight	0.9 lb(US) (0.4 kg)

Environment

Ambient Air Temperature for Storage	-40...176 °F (-40...80 °C)
Relative humidity	15...95 %

Ordering and shipping details

Category	US10I1222335
Discount Schedule	0I12
GTIN	3606486873496
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.756 in (7.000 cm)
Package 1 Width	2.953 in (7.500 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Length	5.315 in (13.500 cm)
Package weight(Lbs)	9.277 oz (263.000 g)
Unit Type of Package 2	S03
Number of Units in Package 2	32
Package 2 Height	11.811 in (30.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	19.800 lb(US) (8.981 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	12 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	5 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	6 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.6 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	28ba494f-ac12-4551-b293-af7901bf5377
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Halogen content performance	Halogen free plastic parts product
PVC free	Yes
Silicon free	Yes

Use Again



Repack and remanufacture

Recyclability potential, in %	18
Circularity Profile	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.