Premises Fiber Optics > Indoor/Outdoor > Tight Buffer > Distribution > 6 Fibers

Dry Block / Indoor/Outdoor / Single Unit / 6 Fibers / SM-A1 / Tight Buffer / OFNR / Black

Part Number: F308-006U13-E991
Status: Made-to-Order
Returnable: Non-Returnable
Minimum Order Quantity: 6 Boxes





MADE IN THE USA

RoHS

GENERAL SPECIFICATIONS

Configuration	Single Unit
Cable Configuration	Flexible tight buffer material extruded over fiber to 900 µm diameter; color coded fibers are combined with dielectric aramid yarns for strength and water-blocking
Jacket	PVC
Fiber Buffer Type	900 µm
Fiber Technology	TeraFlex® Bend Resistant
Fiber Specification	G.657.A1
Bend Insensitive	Yes

COMPLIANCE & SUSTAINABILITY

Standards Compliance	UL 1651 CSA C22.2 No. 232 UL 1666 Telcordia® GR-20-CORE, Issue 3 – Water Penetration ANSI/ICEA S-104-696-2001 ANSI/TIA-568.3-D RoHS-compliant/RoHS 2-compliant
NRTL Programs	UL, c(UL) Listed OFNR UL, c(UL) Listed Sunlight Resistant

PHYSICAL CHARACTERISTICS

Nominal Diameter in (mm)	0.23 (5.8)
Nominal Weight lbs/kft (kg/km)	21 (31)
Max. Tensile Loading Install lbs (N)	300 (1,340)
Max. Tensile Loading Long Term lbs (N)	90 (402)
Min. Bend Radius Install in (mm)	9.1 (232)
Min. Bend Radius Long Term in (mm)	4.6 (116)
Package Type	Wood Reel
Operating Temp. Range	-40°F to +167°F (-40°C to +75°C)
Storage/Shipping Temp. Range	-40°F to +167°F (-40°C to +75°C)
Installation Temp. Range	-4°F to +149°F (-20°C to +65°C)

Product Description

The Superior Essex Dry Block, Sunlight Resistant Indoor/Outdoor riser cable is designed to survive the toughest installation and environmental conditions. The core is fully water-blocked using SAP dry block technology, preventing water ingress from OSP splice enclosures, and the tough thermoplastic jacket is sunlight resistant. GRP and aramid yarn dielectric strength elements give the cable both strength and flexibility. Suitable for intra- and inter-building backbones, conduit, duct and tray pathways, and dry or wet locations. Meets or exceeds ANSI/ICEA S-104-696-2001; OFNR riser listed. Part number F308-006U13-E991 is the riser-rated (OFNR) black version: a 6-fiber OS2 G.657.A1 single mode single-unit distribution cable with 900 µm tight buffer fibers, TeraFlex® Bend Resistant fiber and a PVC jacket. Nominal diameter is 0.23 (5.8) in (mm) with an approximate weight of 21 (31) lbs/kft (kg/km), supplied on a wood reel.

Applications

- Intra/inter-building backbones
- Trench/conduit/duct/tray pathways
- Dry or wet locations

Features

- UL Certified Environmental Product Declaration (EPD)
- Health Product Declaration™ (HPD™)
- Exceeds ANSI/TIA-568.3-D optical performance
- Dry-block design meets ICEA 696 water-blocking requirements
- 900 µm tight-buffered fibers

Benefits

- Contributes toward 1 LEED point under the Material and Resources credit (MRc)
- Contributes toward 1 LEED point under the MRc
- Future-proof fiber performance for current and future multi-gigabit applications
- Cable integrity maintained even if damage occurs to protective layers
- Attaches directly to mechanical connectors

*© 2025 Superior Essex Inc. All information, content, data, specifications, packaging and part numbers detailed herein are subject to change. Purchase of this product is subject exclusively to the then current **Superior Essex Inc. Terms and Conditions of Sale for Communications Cable, Wire and Connectivity Products.***

- UL/NEC Listed OFNR
- All dielectric
- Jacket rip cord
- Black, UL Listed sunlight resistant outer jacket
- BrakeBox® payout control system
- Eliminates the need to purchase separate cables for OSP and indoor/riser applications
- No additional grounding materials need to be purchased
- Saves time in cable preparation
- Long periods of direct sunlight exposure will not damage cable
- Adjustable tension control on reel prevents over spin and entangling of cable

Technical Guideline

Technical Guideline TG099 "Optical Fiber Specifications" provides detailed optical fiber performance specifications, including attenuation, dispersion, supportable Ethernet distances, and standards compliance. Click here for more information.

SUSTAINABILITY CERTIFICATIONS

© 2025 Superior Essex Inc. All information, content, data, specifications, packaging and part numbers detailed herein are subject to change. Purchase of this product is subject exclusively to the then current **Superior Essex Inc. Terms and Conditions of Sale for Communications Cable, Wire and Connectivity Products.**