



### Main

Range of Product	PacDrive 3
Product or Component Type	Single drive
Device short name	LXM 62

### Complementary

Product compatibility	Servo motor SHS Servo motor SH3 2.76 in (70 mm), 2 optimized in terms of torque and speed Servo motor SH3 2.76 in (70 mm), 3 optimized in terms of torque and speed Servo motor SH3 3.94 in (100 mm), 1 optimized in terms of torque and speed Servo motor SH3 3.94 in (100 mm), 2 optimized in terms of torque and speed Servo motor SH3 3.94 in (100 mm), 2 optimized in terms of high torque Servo motor SH3 3.94 in (100 mm), 3 optimized in terms of high torque Servo motor SH3 5.51 in (140 mm), 1 optimized in terms of high torque Servo motor MH3 2.76 in (70 mm), 2 optimized in terms of torque and speed Servo motor MH3 2.76 in (70 mm), 3 optimized in terms of torque and speed Servo motor MH3 3.94 in (100 mm), 1 optimized in terms of torque and speed
Phase	Three phase
[Us] rated supply voltage (through power supply module)	400 V - 10...10 %three phase 230 V - 10...10 %three phase 230 V - 10...10 %single phase
Supply frequency	50/60 Hz - 5...5 %
Continuous output current	5 A 4 kHz
Output current 3s peak	15 A 4 kHz
Continuous power	2.4 kW
Nominal power	2.4 kW
Switching frequency	8 kHz
Overvoltage category	III
Electrical connection	Terminal 0.2...15 mm <sup>2</sup> , AWG 24...AWG 16 CN4) Terminal 0.5...16 mm <sup>2</sup> , AWG 20...AWG 6 CN5) Terminal 0.75...16 mm <sup>2</sup> , AWG 18...AWG 6 CN6) Terminal 0.2...6 mm <sup>2</sup> , AWG 24...AWG 10 CN7)
Tightening torque	CN1 22.13 lbf.in (2.5 N.m)
Number of inputs	2 digital 2 touch probe
Discrete input voltage	24 V DC for - 20...25 %
Number of outputs	2 digital
Discrete output voltage	24 V DC
Safety function	STO (safe torque off)
Communication interface	SERCOS III, Integrated
Depth	10.63 in (270 mm)
Height	12.20 in (310 mm)
Width	1.75 in (44.5 mm)
Net Weight	6.61 lb(US) (3 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

Standards	CSA C22.2 No 14 IEC 61800-5-1 ISO 13849-1 ISO 13849-2 UL 508C IEC 62061 IEC 61508 IEC 62061 IEC 61800-5-2 IEC 61800-3
Product Certifications	CSA[RETURN]TÜV[RETURN]CE[RETURN]EAC[RETURN]JUL
IP degree of protection	IP20 IEC 60529
Vibration resistance	10 m/s <sup>2</sup> IEC 60721-3-3
Shock resistance	100 m/s <sup>2</sup> IEC 60721-3-3
Pollution degree	2 IEC 61800-5-2
Environmental characteristic	3K3 IEC 60721-3-3
Relative humidity	5...85 %
Ambient Air Temperature for Operation	41...131 °F (5...55 °C)

## Ordering and shipping details

Category	18356-PACDRIVE3 LEXIM62 SERVO DRIVES
Discount Schedule	PC52
GTIN	3606485317724
Returnability	No
Country of origin	DE

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.02 in (10.2 cm)
Package 1 Width	12.80 in (32.5 cm)
Package 1 Length	16.73 in (42.5 cm)
Package 1 Weight	8.44 lb(US) (3.828 kg)
Unit Type of Package 2	S06
Number of Units in Package 2	10
Package 2 Height	29.53 in (75.0 cm)
Package 2 Width	23.62 in (60.0 cm)
Package 2 Length	31.50 in (80.0 cm)
Package 2 Weight	113.05 lb(US) (51.28 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
PVC free	Yes