


Product data sheet

Specifications

SQUARE D



Overload Relay, Type S, melting alloy, separate mount overload, NEMA size 00, 0, 1, 3 pole, 3 phase, 25A, 600VAC

9065SE05

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	Separate Mounting
Thermal overload type	Melting alloy

Complementary

NEMA size	1
Number of thermal units required	3
Mounting Support	Panel
[Ue] rated operational voltage	600 V AC
Height	3.3 in (84.1 mm)
Width	3.5 in (89.7 mm)
Depth	4.0 in (100.8 mm)

Ordering and shipping details

Category	US10CP121661
Discount Schedule	0CP1
GTIN	785901878827
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.60 in (11.684 cm)
Package 1 Width	5.30 in (13.462 cm)
Package 1 Length	5.20 in (13.208 cm)
Package 1 Weight	16.320 oz (462.664 g)

Contractual warranty

Warranty	18 months
----------	-----------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.


Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.


[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Not compliant
California proposition 65	"WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov "

Use Again

 Repack and remanufacture	
Take-back	No