

Specifications



Photo is representative

Eaton WSRDW33542CH-S901

Eaton Crouse-Hinds series Arktite WSRD interlocked receptacle with enclosed safety disconnect switch, 30A, 3-wire, 4-pole, Brass contacts, Windowed door, Non-fused, Style 2, Cutler-Hammer, 304 stainless steel, Spring door, 480/600 Vac

General specifications

PRODUCT NAME	Eaton Crouse-Hinds series Arktite WSRD interlocked receptacle with enclosed safety disconnect switch
CATALOG NUMBER	WSRDW33542CH-S901
PRODUCT LENGTH/DEPTH	8.94 in
PRODUCT HEIGHT	23.43 in
PRODUCT WIDTH	10.21 in
PRODUCT WEIGHT	27 lb



Certifications and compliances

AREA CLASSIFICATION Ordinary/Non-Hazardous

Product specifications

ENCLOSURE TYPE With switch

	Locations
STANDARDS TYPE	NEC/CEC
NEMA RATING	4 4X

DOOR STYLE	Windowed
AMPERAGE RATING	30A
FUSING	Non-fused
GROUNDING STYLE	Style 2
CONFIGURATION	Three-wire, four-pole
MATERIAL	304 stainless steel
CONTACT MATERIAL	Brass
VOLTAGE RATING	480 Vac/600 Vac
MANUFACTURER	Cutler-Hammer
RECEPTACLE STYLE	Spring door

Resources

BROCHURES	Arkite WSRD Interlock with Eaton Switch
CATALOGUES	Arkite WSR/WSRD Interlock Receptacles catalog page
CERTIFICATION REPORTS	Arkite WSR/WSRD Interlock Receptacles with Enclosed Disconnect Switches UL certification Arkite WSR/WSRD Interlock Receptacles with Enclosed Disconnect Switches Canadian certification
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - WSRDW33542CH-S901

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

Follow us on social media to get the latest product and support information.

All other trademarks are property of their respective owners.

