



SEE NOTE 1

SEE NOTE 2

11 SEE NOTE 3

9 SEE NOTE 1

NOTE:
 1/ TORQUE 1/4-20 BOLTS TO 60 TO 72 IN. LBS.
 2/ TORQUE 1/2-13 BOLTS TO 360 TO 430IN. LBS.
 3/ CLAMPED BETWEEN ITEM 3 AND ITEM 4.

	GENERAL TOLERANCE SPEC. 48050-040-50 NORMAL CLASS TOLERANCE	SQUARE D Schneider Electric	
	DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED * OR (ST) * DENOTES CRITICAL CHARACTERISTIC <small>SQUARE D/SCHNEIDER ELECTRIC HAS PROPRIETARY RIGHTS TO THE INFORMATION CONTAINED HEREON. THIS INFORMATION REMAINS THE PROPERTY OF SQUARE D/SCHNEIDER ELECTRIC AND MAY BE REPRODUCED OR USED ONLY IN ACCORDANCE WITH INSTRUCTIONS OR PERMISSION FROM SQUARE D/SCHNEIDER ELECTRIC. THIS DOCUMENT SHALL BE RETURNED TO SQUARE D/SCHNEIDER ELECTRIC UPON REQUEST. USER SHOULD VERIFY DRAWINGS ARE THE MOST RECENT VERSION PRIOR TO USE. © 2006, SCHNEIDER ELECTRIC, ALL RIGHTS RESERVED.</small>	WIRING TERMINAL KIT ASSEMBLY 600MSLK	
DATE	28JUL06	ECO	W070358
SIZE B	DWG NO L43B654	SHEET 1 OF 1	

REV.	ECO	DATE	BY	REVISION DESCRIPTION

PRINTS TO: