



GE  
Lighting

### 35788 - Integrated 3ft LED Glass Tubes

#### LED11ET8/G/3/840

- ☞ Convert your existing linear fluorescent fixture to LED lighting without needing a comprehensive reinstall.
- ☞ Each LED tube is outfitted with an internal GE driver.
- ☞ The GE integrated LED tubes run on electronic T8 instant-start or programmed start ballasts.
- ☞ 66% longer life than LFL (50,000 vs. 30,000 hours)
- ☞ No UV
- ☞ Easy disposal, non-hazardous waste
- ☞ Check ballast compatibility at [www.gelighting.com/LEDTUBES-ballast-compatibility](http://www.gelighting.com/LEDTUBES-ballast-compatibility)
- ☞ UL Listed

#### Product Photo



#### GENERAL CHARACTERISTICS

Product Technology	LED
Rated Life (Hours)	50000 h
Base	G13
Bulb Shape	T8

#### PHOTOMETRIC CHARACTERISTICS

Initial Lumens-nominal	1500 lm
Color Rendering Index-CRI	80
Color Temperature	4000 K

#### PRODUCT INFORMATION

Product Code	35788
Description	LED11ET8/G/3/840
Alternative Unit Of Measure	EACH
Standard Package Quantity	20
Ean UPC	043168357883
Standard Package GTIN	00043168357883
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	20
Sales Unit	Each
UCC	043168357883
Alternative Unit Of Measure	CASE
Standard Package Quantity	20
Ean UPC	043168357883
Standard Package GTIN	10043168357880
No Of Items Per Sales Unit	
No Of Items Per Standard Package	20
Sales Unit	Case
UCC	043168357883

#### DIMENSIONS

Bulb Max Overall Length-MOL	36.0 in
-----------------------------	---------

#### ELECTRICAL CHARACTERISTICS

Rated power (Watts)	11 W
---------------------	------