

► Model LSWB

Wall Mounting Kit for 4X, Safe Area Applications



Model LSWB wall mounting kit is designed for use with Federal Signal's Type 4X certified, pipe mount warning lights. This kit features a 1/2-inch NPT pipe connection and is supplied with a surface mount weatherproof backbox.


Model LSWB can be wired through either the 1/2-inch or 3/4-inch conduit openings located on the weatherproof backbox. Additional bushings are available to purchase for 3/4-inch and 1-inch fixture mounting (K2881358A). Terminal block kit (KIT-WBTB) enables users to easily terminate wires from the beacon within the backbox of the LSWB bracket.

Model LSWB is ideal for use in 4X, IP66, and indoor or outdoor applications. It is compatible with the following Federal Signal models: 225, 121ALED, 121SLED, 371LED, FB24ST, FB24STHI, FB24STHI-CN, FB2LED, FB2PST and FB2PST-I.

F E A T U R E S

- For wall mount applications
- Heavy-duty construction
- Easy installation
- Provides 1/2-inch NPT standard pipe mount
- Indoor and outdoor use
- Ideal for use in 4X, IP66 environments
- IP69K Compliant

Wall Mounting Kit for 4X, Safe Area Applications (LSWB)



SPECIFICATIONS

Operating Temperature:	-58°F to 150°F	-50°C to 66°C
Net Weight:	2.0 lbs	0.91 kg
Shipping Weight:	2.3 lbs	1.04 kg
Height:	6.78"	172.2 mm
Width:	5.64"	143.3 mm
Depth:	6.76"	171.7 mm

HOW TO ORDER

Specify Model:**LSWB** – Wall Mounting Kit, 4X, Safe Areas

OPTIONAL ACCESSORIES

Description	Part Number
Terminal Block Kit (8 connector)	KIT-WBTB
Hardware Kit*	K2881358A
* Hardware Kit includes: Steel Bushing 3/4" x 1/2" Steel Bushing 1" x 3/4" Rigid Conduit 1/2" NPT 3" Length Nylon Screw Collar	