

	Catalogue Number	Alternate Cat. No.	Size or Description	Packaging Case	Box	
Combination Coupling						
	4157-DC	Coupling used to join duplex 14/2 to 10/3 armored or MC cable to 3/4" EMT	1/2" with 3/4" KO	100	25	
Flex Connector - Zinc Die Cast						
	802-DC2	Range A/C - M/C min: .480" max: .580"	3/8" single screw	250	25	
Flex Connector - Zinc Die Cast						
	545-DC2	Range A/C - M/C min: .410" max: .610"	3/8"	1000	100	
One Screw Connectors (L-series) for BX, Flex, NM - Zinc						
	L-16	-	3/8" (1/2" KO)	Skid Qty. 28,000	500	50
	L-17	BL-17	1/2"	11,200	250	25
	L-18	BL-18	3/4"	9,600	200	20
	L-19	BL-19	1"	4,800	100	10
SNAP-IN - Strap-Type L-16 Connector - steel press bar						
	560SP	-	3/8" (1/2" KO)	28,000	500	50
PVC "Snap in" Connector						
	618-NM		14/2 to 10/3 (1/2"KO)	3000	100	
	618-NMB		14/2 to 10/3 (1/2"KO)	300 pcs in a Jar		
	618-NMC		14/2 to 10/3 (1/2"KO)	BULK - 3,000/case		
	RC75		8/3 to 6/3 (3/4"KO)	500	50	
	RC75J		8/3 to 6/3 (3/4"KO)	165 in a Jar		
1-Screw Duplex Connector - Zinc Die Cast						
	350	601-DC2	3/8" with 2 x 1/2" Flex	200	20	
	621-DC2		3/4" with 2 x 1/2" Flex	100	25	
2-Screw Duplex Connector - Zinc Die Cast						
	360	602-DC2	3/8" With 1/2" Knock out	250	25	
90° Duplex Connector - Zinc Die Cast						
	561A	830-DC2	3/8" With 1/2" Knock out	250	25	
Snap In 90° Duplex Connector - Zinc Die Cast						
	84690SP		3/8" With 1/2" Knock out	250	25	
Squeeze Strap Type Connector						
	653-DC2		.620 - .780 MC (1/2"KO)	250	25	