



Wiremold

400, 800, 2300, 2300D Series™ Nonmetallic Raceway Systems

Small, Two-Piece, Nonmetallic Raceway Systems Ideal for Low Voltage and Power Applications

Wiremold® 400, 800, and 2300 Series™ Raceways, are a family of single compartment raceway systems designed for communication or power applications. Ideal for use in classrooms, offices, hotel applications, or anywhere a small, secure, low profile raceway is needed. The 2300BACD Nonmetallic Divided Raceway is ideal for use when power and low voltage cabling are needed in a single raceway.




400, 800, 2300, and 2300D
Series Raceway Profiles

FEATURES & BENEFITS

- **Accommodates communication and/or power wiring.** Can be used for communications, computer lines, surveillance systems, fire alarms, outlets, and more.
- **Available in three sizes.** 400BAC, 800BAC, and 2300BAC sizes provide flexibility for meeting a variety of capacity requirements. Perfect for most small drops and horizontal runs to work stations.
- **Durable, textured PVC ivory or white finish.** Blends with any decor. Paintable using latex paint. Consult factory for custom color options.
- **Single- and dual-compartment low profile design.** Provides functionality and flexibility with aesthetics for single- or dual-service applications.
- **Adhesive backing for low voltage (under 50V) applications.** Allows base to be pressed onto mounting surface. Speeds installation.
- **Lightweight and easy to handle.** Saves time and labor costs. Standard 5' [1.525m] raceway lengths can be easily installed by one person. Custom lengths up to 10' [3.05m] are also available.
- **Divided FiberReady® fittings.** For use with 2300BAC and 2300BACD. Full capacity fittings provide 2" [51mm] bend radius.
- **Over-the-raceway box for 2300 and 2300D.** Boxes mount over continuous run of raceway base eliminating the need to cut raceway when locating devices.
- **Sure-Snap® boxes for 2300BACD.** Provides flush look and ease of installation.
- **Snap-on cover.** Provides security with access to wiring for changes or additions.
- **Datacom connectivity options.** Accepts industry standard and proprietary devices from a wide range of manufacturers to provide a seamless and aesthetically pleasing interface for voice, data, audio, and video applications at the point of use.
-  **UL** Listed File E90378 Raceway, E90377 Fittings.

400, 800, 2300, 2300D Series Raceway System Layout



NOTE: Illustration shows product applications only. 2315 Tee Fitting cannot be used with 2300D Divided Raceway.

400, 800, 2300, 2300D Raceway Series Wire Fill Capacities for Power

WIRE SIZE THHN/THWN	O.D.		400BAC	NUMBER OF CONDUCTORS			2300BACD†
	Inches	[mm]		800BAC	2300BAC		
14 AWG	0.111	[2.8]	5	6	15		7
12 AWG	0.130	[3.3]	3	5	14		6
10AWG	0.164	[4.2]	0	4	12		5

400, 800, 2300, 2300D Raceway Series Wire Fill Capacities for Communications

	CABLE/WIRE SIZE	O.D.		40% FILL*			
		inches	[mm]	400	800	2300	2300D†
UNSHIELDED TWISTED PAIR	4-Pair, 24 AWG Cat. 3	0.190	[4.8]	1	3	11	5
	4-Pair, 24 AWG Cat. 5e	0.210	[5.3]	1	3	9	4
	4-Pair, 24 AWG Cat. 6	0.250	[6.3]	1	2	6	3
	4-Pair, 24 AWG Cat. 6a**	0.354	[9.0]	0	1	3	1
	25-Pair, 24 AWG	0.410	[10.4]	0	0	2	1
COAXIAL	RG6/U	0.270	[6.9]	0	1	5	2
FIBER	Zip Cord 0.118 x 0.157	[3 x 6]	1	3	12	6	
	Round 4 Strand Fiber	0.187	[4.8]	1	3	12	6
	Round 6 Strand Fiber	0.256	[6.5]	1	2	6	3

* Wire capacity is reduced to allow for proper conductor bend radius and maximum permissible heat rise.







** Category 6 augmented (6a) cable for 10 gigabit ethernet – max allowed cable diameter per addenda No. 11 ANSI TIA/EIA 568-B.2.

† each compartment.

400BAC, 800BAC, 2300BAC, 2300BACD Series Raceway Ordering Information







Catalog No./Item	Description/Specifications
400BAC 800BAC 2300BAC 2300BACD	400BAC-WH 800BAC-WH 2300BAC-WH 2300BACD-WH Low profile, two-piece raceway with snap-on cover – Available in 5' [1.525m] and length. Supplied with wide adhesive tape along entire length of base.
400BAC 800BAC 2300BAC 2300BACD	

400, 800, 2300, 2000D Series Fittings Ordering Information









Catalog No./Item	Description/Specifications																
400WC 800WC 2300WC	Wire Clip – For holding conductors in place.  <table><tr><th>CAT NO.</th><th>A</th></tr><tr><td>400WC</td><td>1/2" [12.7mm]</td></tr><tr><td>800WC</td><td>1" [25mm]</td></tr><tr><td>2300WC</td><td>1" [25mm]</td></tr></table>	CAT NO.	A	400WC	1/2" [12.7mm]	800WC	1" [25mm]	2300WC	1" [25mm]								
CAT NO.	A																
400WC	1/2" [12.7mm]																
800WC	1" [25mm]																
2300WC	1" [25mm]																
406 806 2306	Cover Clip – For covering joint where two pieces of 400BAC, 800BAC or 2300BAC Series Raceway cover come together.  <table><tr><th>CAT NO.</th><th>A</th></tr><tr><td>406</td><td>13/16" [20.6mm]</td></tr><tr><td>806</td><td>1" [25mm]</td></tr><tr><td>2306</td><td>2" [51mm]</td></tr></table>	CAT NO.	A	406	13/16" [20.6mm]	806	1" [25mm]	2306	2" [51mm]								
CAT NO.	A																
406	13/16" [20.6mm]																
806	1" [25mm]																
2306	2" [51mm]																
410B 810B 2310B	Blank End Fitting – For closing open end of 400BAC, 800BAC, or 2300BAC Raceway Series.  <table><tr><th>CAT NO.</th><th>A</th><th>B</th><th>C</th></tr><tr><td>410B</td><td>13/16" [20.6mm]</td><td>1/2" [12.7mm]</td><td>3/8 [9.5mm]</td></tr><tr><td>810B</td><td>1 1/4" [32mm]</td><td>1/2" [12.7mm]</td><td>3/8 [9.5mm]</td></tr><tr><td>2310B</td><td>2 1/4" [57mm]</td><td>1" [25mm]</td><td>3/8 [9.5mm]</td></tr></table>	CAT NO.	A	B	C	410B	13/16" [20.6mm]	1/2" [12.7mm]	3/8 [9.5mm]	810B	1 1/4" [32mm]	1/2" [12.7mm]	3/8 [9.5mm]	2310B	2 1/4" [57mm]	1" [25mm]	3/8 [9.5mm]
CAT NO.	A	B	C														
410B	13/16" [20.6mm]	1/2" [12.7mm]	3/8 [9.5mm]														
810B	1 1/4" [32mm]	1/2" [12.7mm]	3/8 [9.5mm]														
2310B	2 1/4" [57mm]	1" [25mm]	3/8 [9.5mm]														
411*	90° Flat Elbow – For right angle turns on same surface. 																
415*	Tee – For branches at right angles. 																
417*	Internal Elbow – For surfaces at right angles. 																

NOTE: No suffix denotes ivory finish. Add “-WH” suffix for white finish.

* For 2300BAC and 2300BACD Raceway must be mitered to use 2311 and 2318. 2315 cannot be used in divided raceway.




Catalog No./Item	Description/Specifications									
418 818 2318*	90° External Elbow – For right angle turns around external corners.  <table><tr><th>CAT NO.</th><th>A</th></tr><tr><td>418</td><td>1 1/2 [38mm]</td></tr><tr><td>818</td><td>2" [51mm]</td></tr><tr><td>2318</td><td>2 1/2" [64mm]</td></tr></table>	CAT NO.	A	418	1 1/2 [38mm]	818	2" [51mm]	2318	2 1/2" [64mm]	
CAT NO.	A									
418	1 1/2 [38mm]									
818	2" [51mm]									
2318	2 1/2" [64mm]									
PVC-1	PVC Cutter – Regular duty cutter. Ideal for use with small nonmetallic raceway. 									
810A2	Entrance End Fitting – For connecting 400 or 800 Series Raceway with 1/2" trade size conduit or armored cable. 1/2" trade size KO on end and bottom. 									
811 2311* **	90° Flat Elbow – For right angle turns on same surface.  <table><tr><th>CAT NO.</th><th>A</th></tr><tr><td>811</td><td>2 1/2" [64mm]</td></tr><tr><td>2311</td><td>4 3/16"[106mm]</td></tr></table>	CAT NO.	A	811	2 1/2" [64mm]	2311	4 3/16"[106mm]			
CAT NO.	A									
811	2 1/2" [64mm]									
2311	4 3/16"[106mm]									
815 2315* **	Tee – For right angles turns on same surface.  <table><tr><th>CAT NO.</th><th>A</th><th>B</th></tr><tr><td>815</td><td>4 1/8" [105mm]</td><td>2 3/4" [70mm]</td></tr><tr><td>2315</td><td>6" [152mm]</td><td>4 1/8" [105mm]</td></tr></table>	CAT NO.	A	B	815	4 1/8" [105mm]	2 3/4" [70mm]	2315	6" [152mm]	4 1/8" [105mm]
CAT NO.	A	B								
815	4 1/8" [105mm]	2 3/4" [70mm]								
2315	6" [152mm]	4 1/8" [105mm]								
817 2317*	Internal Elbow – For surfaces at right angles.  <table><tr><th>CAT NO.</th><th>A</th></tr><tr><td>817</td><td>2" [51mm]</td></tr><tr><td>2317</td><td>2 1/2" [64mm]</td></tr></table>	CAT NO.	A	817	2" [51mm]	2317	2 1/2" [64mm]			
CAT NO.	A									
817	2" [51mm]									
2317	2 1/2" [64mm]									
889A	Reducing Connector (800-400) – For transitioning from 800 to 400 Series Raceway. 									

400, 800, 2300, 2000D Series Fittings Ordering Information (continued)

Catalog No./Item	Description/Specifications	Catalog No./Item	Description/Specifications
2310A 	Entrance End Fitting – 1/2", 3/4", and 1" trade size KOs for feeding 2300 Series Raceway.	2318DFO 	Bend Radius Divided External Elbow – A 90° external corner with integral dividers to provide 2" [51mm] cable bend radius for UTP and fiber optic installations.
2310DFO 	Bend Radius Divided Entrance End Fitting – Divided fitting to feed 2300BAC and 2300BACD Series Raceway. Includes 1/2", 3/4" and 1" trade size KOs on back and top.	2389 	Reducing Connector (2300BAC-800BAC) – For transitioning from 2300BAC to 800BAC Series Raceway.
2311DFO 	Bend Radius Divided Flat Elbow – A 90° flat corner with integral dividers to provide 2" [51mm] cable bend radius for UTP and fiber optic installations.	2389A 	Reducing Connector (2300BAC-400BAC) – For transitioning from 2300BAC to 400BAC Series Raceway.
2317DFO 	Bend Radius Divided Internal Elbow – A 90° internal corner with integral dividers to provide 2" [51mm] cable bend radius for UTP and fiber optic installations.	5474 	Transition Tap Fitting – Makes transition from 5400 Raceway to 400BAC, 800BAC, 2300BAC Series Raceway.

NOTE: No suffix denotes ivory finish. Add "-WH" suffix for white finish.

400, 800, 2300, 2000D Series Communications Boxes Ordering Information (continued)

Catalog No./Item	Description/Specifications	Catalog No./Item	Description/Specifications
CM-MMB-231 	One Insert Multimedia Box – Compatible with 400BAC and 800BAC Series Raceway. Accepts Pass & Seymour® Activate Inserts and Wiremold Open System Communication Modules.	CM-MMB-233 	Three-Insert FiberReady® Multimedia Box – Compatible with 400BAC, 800BAC and 2300BAC Series Raceway. Accepts Pass & Seymour® Activate Inserts and Wiremold Open System Communications Modules
CM-MMB-232 	Two Insert FiberReady® Multimedia Box – Compatible with 400BAC, 800BAC, and 2300BAC Series Raceway. Accepts Pass & Seymour® Activate Inserts and Wiremold Open System Communications Modules.		


400, 800, 2300 Series Raceway Sure-Snap® Device Boxes


- **Interchangeable covers and bases.** Provides installation flexibility.
- **Large knockout.** Accommodates many cable types and quantities.
- **Cover removes easily.** One twist of a screwdriver removes the cover for fast changes.
- **No screws to assemble.** The secure snap assembly requires fewer tools and parts, which means a shorter installation time.




Sure-Snap Device Boxes are available in a variety of sizes and depths.


400, 800, 2300 Series Raceway Sure-Snap® Device Boxes Ordering Information (For Non-Divided Raceways)


Catalog No./Item	Description/Specifications															
2344 2344-2 	Extra Deep Device Box – 2344 one-gang, 2344-2 two-gang. 2344-2 base has rectangular KO to enable extension from existing single-gang flush wall box and 1/2" and 1" trade size concentric KOs. Accepts NEMA Faceplates <table> <tr> <th>CAT #</th><th>GANG(s)</th><th>A</th><th>B</th><th>C</th></tr> <tr> <td>2344</td><td>1</td><td>4 3/4" [121mm]</td><td>3" [76mm]</td><td>2 3/4" [70mm]</td></tr> <tr> <td>2344-2</td><td>2</td><td>4 3/4" [121mm]</td><td>4 7/8" [124mm]</td><td>2 3/4" [70mm]</td></tr> </table>	CAT #	GANG(s)	A	B	C	2344	1	4 3/4" [121mm]	3" [76mm]	2 3/4" [70mm]	2344-2	2	4 3/4" [121mm]	4 7/8" [124mm]	2 3/4" [70mm]
CAT #	GANG(s)	A	B	C												
2344	1	4 3/4" [121mm]	3" [76mm]	2 3/4" [70mm]												
2344-2	2	4 3/4" [121mm]	4 7/8" [124mm]	2 3/4" [70mm]												

2347 2347-2 	Device Box – 2347 one-gang, 2347-2 two-gang. For standard switches and devices. 2347 and 2347-2 Bases have rectangular KO to enable extension from existing flush wall box and 1/2" and 1" trade size concentric KOs. Accepts NEMA Faceplates <table> <tr> <th>CAT #</th><th>GANG(S)</th><th>A</th><th>B</th><th>C</th></tr> <tr> <td>2347</td><td>1</td><td>4 3/4" [121mm]</td><td>3" [76mm]</td><td>1 3/8" [35mm]</td></tr> <tr> <td>2347-2</td><td>2</td><td>4 3/4" [121mm]</td><td>4 7/8" [124mm]</td><td>1 3/8" [35mm]</td></tr> </table>	CAT #	GANG(S)	A	B	C	2347	1	4 3/4" [121mm]	3" [76mm]	1 3/8" [35mm]	2347-2	2	4 3/4" [121mm]	4 7/8" [124mm]	1 3/8" [35mm]
CAT #	GANG(S)	A	B	C												
2347	1	4 3/4" [121mm]	3" [76mm]	1 3/8" [35mm]												
2347-2	2	4 3/4" [121mm]	4 7/8" [124mm]	1 3/8" [35mm]												



NOTE: No suffix denotes ivory finish. Add “-WH” suffix for white finish.
All single-gang bases have a rectangular knockout on the base.

Catalog No./Item	Description/Specifications																				
2348 2348-2 2348-3 	Deep Device Box – 2348 one-gang, 2348-2 two-gang, 2348-3 three-gang. For deeper switches and devices. 2348, 2348-2, and 2348-3 Bases have rectangular KO to enable extension from existing flush wall box and 1/2" and 1" concentric KOs. Accepts NEMA Faceplates. <table> <tr> <th>CAT #</th><th>GANG(S)</th><th>A</th><th>B</th><th>C</th></tr> <tr> <td>2348</td><td>1</td><td>4 3/4" [121mm]</td><td>3" [76mm]</td><td>1 3/4" [35mm]</td></tr> <tr> <td>2348-2</td><td>2</td><td>4 3/4" [121mm]</td><td>4 7/8" [124mm]</td><td>1 3/4" [44mm]</td></tr> <tr> <td>2348-3</td><td>3</td><td>4 3/4" [121mm]</td><td>7" [178mm]</td><td>1 3/4" [44mm]</td></tr> </table>	CAT #	GANG(S)	A	B	C	2348	1	4 3/4" [121mm]	3" [76mm]	1 3/4" [35mm]	2348-2	2	4 3/4" [121mm]	4 7/8" [124mm]	1 3/4" [44mm]	2348-3	3	4 3/4" [121mm]	7" [178mm]	1 3/4" [44mm]
CAT #	GANG(S)	A	B	C																	
2348	1	4 3/4" [121mm]	3" [76mm]	1 3/4" [35mm]																	
2348-2	2	4 3/4" [121mm]	4 7/8" [124mm]	1 3/4" [44mm]																	
2348-3	3	4 3/4" [121mm]	7" [178mm]	1 3/4" [44mm]																	

2348S/51 	Shallow Device Box / Extension Box – For shallow switches and receptacles. Base has rectangular KO. Accepts NEMA Faceplates.
--	--

2348AMP 	Magnetic Deep Device Box (with Grommet) – For deeper switches and devices. Magnetic backing. Base has rectangular KO. Accepts NEMA Faceplates
---	---

400, 800, 2300 Series Raceway Round Fixture Boxes for Non-Divided Raceway Ordering Information




Item	Description	Cat. No.	Diameter	Depth	Specifications
	Blank Cover	2336	4 1/2" [114mm]	—	Use with any round nonmetallic device box to convert into junction box.
	Round Extension Box	2337A	5 1/2" [140mm]	1" [25mm]	For hanging fixtures, smoke/fire alarms and other security devices with 3 1/2" [89mm] or 4 1/16" [103mm] mounting centers. 5 1/2" [140mm] diameter with open base. Not for use with ceiling fans.
	Fixture Box	2338A	5 1/2" [140mm]	1" [25mm]	For hanging smoke/fire alarms and other security devices with 3 1/2" [89mm] or 4 1/16" [103mm] mounting centers. Not for use with ceiling fans.

NOTE: No suffix denotes ivory finish. Add “-WH” suffix for white finish.


Sure-Snap® Device Boxes for 2300BACD Divided Series Raceway

The 2300BAC and 2300BACD Series Divided Raceway Box family provides two unique benefits; labor savings with “over-the-raceway” installation and Sure-Snap® device boxes. The 2348D and 2344D “over-the-raceway” design eliminates cutting the raceway base to mount boxes. The base snaps on anywhere along the raceway. The Sure-Snap integral device box of the 2344SD-2A combines aesthetics with labor savings. 5507 Series Faceplates, Pass & Seymour Activate Inserts, Wiremold Open System Communication Modules and Ortronics Series II and TracJack Modules snap directly into the Sure-Snap Device Box, eliminating the need for additional faceplates. The single-gang boxes accept standard NEMA faceplates.















Sure-Snap® Device Boxes for 2300BACD Divided Series Raceway Ordering Information

Catalog No./Item	Description/Specifications	Catalog No./Item	Description/Specifications
2348D 	Device Box – For use with 2300BACD Divided Raceway. For mounting standard switches, receptacles and industry standard faceplates for communication devices. Accepts NEMA Faceplates.	2344SD-2A 	Two-Gang Deep Divided Box – A divided two-gang box for use with 2300D Series Raceway. Provides the ability to have both power and low voltage at a single point of use. Accepts 5507 Series Faceplates, Ortronics® TracJack & Series II Modules, Pass & Seymour® Activate™ Series Inserts, and Wiremold Open System Communication Modules.
2344D 	Extra Deep Device Box – For use with 2300BACD Divided Raceway when additional depth is required. For mounting standard switches, receptacles and industry standard faceplates for communication devices. Accepts NEMA Faceplates.	Note: Not for use with NEMA Faceplates. CM-EPLA End Plates are required when using Wiremold Open System communication modules and Pass & Seymour® Activate inserts. S2-EPL End Plates are required when using Ortronics® Series II inserts. To mount Ortronics® TracJack modules, use 5507-4TJ or 5507-6TJ Faceplates.	

2344SD-2 Over-the-Raceway Box Application



5507 Series Faceplates Ordering Information

Catalog No./Item	Description/Specifications	Catalog No./Item	Description/Specifications
5507AD	 Modular Furniture Adapter – For mounting Activate modular furniture bezels and other modular furniture adapters. Not for use with rectangular (decorator) style devices.	5507RJ	 Dual RJ11/RJ45 Connector Faceplate – For mounting one or two RJ type connectors – has one opening and a KO for the other.
5507B	 Blank Faceplate – For covering unused compartments in the device bracket.	5507FRJ	 Flush Dual RJ11/RJ45 Connector Faceplate – Same as 5507RJ except the connectors are recessed to provide a flush installation.
5507D	 Duplex Receptacle Faceplate – For covering duplex style devices. Accepts 106 Frame.	5507-4TJ	 Ortronics® Faceplate – For mounting Ortronics® datacom inserts. Accepts four TracJack Devices.
5507R	 Rectangular Receptacle Faceplate – For covering rectangular decorator style devices.	5507-6TJ	 Ortronics® Faceplate – For mounting Ortronics® datacom inserts. Accepts six TracJack Devices.
5507S	 Rectangular Spacer – For mounting commercial device plates. Installs between the device bracket and a device.	CM-EPLA	 End Plates – Includes two outlet identification labels with clear covers and two matching screw covers. Required for mounting Pass & Seymour® Activate™ and Wiremold Open System communication modules into the 2344SD-2A.
5507SW	 Switch Faceplate – For covering standard toggle switches.	S2-EPL	 End Plates – Includes two outlet identification labels with clear covers and two matching screw covers. Required for mounting Ortronics® Series II modules into the 2344SD-2A.
5507T1	 Single Receptacle Faceplate – For covering single receptacles – 1.59" [40mm] diameter.		
5507T2	 Single Receptacle Faceplate – For covering single receptacles – 1.41" [36mm] diameter.		

NOTE: No suffix denotes ivory finish. Add “-WH” suffix for white finish, and “G” for Gray finish. Consult factory for custom colors.

 **Wiremold**

60 Woodlawn Street
West Hartford, CT 06110
Phone: 1.877.BY.LEGRAND (295-3472)
Fax: 1.860.232.2062
www.legrand.us/wiremold

570 Applewood Crescent
Vaughan, Ontario L4K 4B4
Phone: 905.738.9195
Fax: 905.738.9721

ED296R16 – Updated January 2013 – For latest specs visit www.legrand.us/wiremold

© Copyright 2013 Legrand/Wiremold All Rights Reserved

