



GE  
Lighting

### 19488 - Integrated 4ft

#### LED26ET5/G/4/865

- ☞ Required T5 HO Ballast
- ☞ Convert your existing linear fluorescent fixture to LED lighting without needing a comprehensive reinstall.
- ☞ Each LED tube is outfitted with an internal GE driver.
- ☞ The GE integrated LED tubes run on electronic T5 instant-start or programmed start ballasts.
- ☞ Longer life than LFL (50,000 vs. 30,000 hours)
- ☞ Easy disposal, non-hazardous waste
- ☞ UL Listed

#### Product Photo



#### GENERAL CHARACTERISTICS

Base Description	LED_Bs_G5
Base Type	G5
Product Technology	LED
Rated Life (Hours)	50000 h
LED Tube Type	Glass
Environmental Rating	LED_Tube_Glass

#### PHOTOMETRIC CHARACTERISTICS

Initial Lumens-nominal	3800 lm
Color Rendering Index-CRI	80
Color Temperature	6500 K

#### PRODUCT INFORMATION

Product Code	19488
Description	LED26ET5/G/4/865
Alternative Unit Of Measure	EACH
Standard Package Quantity	20
Ean UPC	043168194884
Standard Package GTIN	00043168194884
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	20
Sales Unit	Each
UCC	
Alternative Unit Of Measure	CASE
Standard Package Quantity	20
Ean UPC	043168194884
Standard Package GTIN	10043168194881
No Of Items Per Sales Unit	
No Of Items Per Standard Package	20
Sales Unit	Case
UCC	

#### DIMENSIONS

Bulb Max Overall Length-MOL	48.0 in
-----------------------------	---------

#### ELECTRICAL CHARACTERISTICS

Rated power (Watts)	25 W
---------------------	------