

DPEAN11

Auxiliary contact block, Easy TeSys DPE, 1NO +1NC



Main

Range	Easy TeSys
Device short name	DPEAN
Product or Component Type	Auxiliary contact block
Range compatibility	Easy TeSys Easy TeSys DPE contactor
Auxiliary contact composition	1 NO + 1 NC
Auxiliary contacts operation	Instantaneous
[Ue] rated operational voltage	690 V AC 25...400 Hz
[Ui] rated insulation voltage	690 V IEC 60947-5-1 600 V UL 600 V CSA
[I _{th}] conventional free air thermal current	10 A (at 140 °F (60 °C))
Irms rated making capacity	140 A AC conforming to IEC 60947-5-1 250 A DC conforming to IEC 60947-5-1
Permissible short-time rating	100 A 140 °F (60 °C) 1 s 120 A 140 °F (60 °C) 500 ms 140 A 140 °F (60 °C) 100 ms

Complementary

Minimum switching current	5 mA
Minimum switching voltage	17 V
Insulation resistance	> 10 MOhm
Associated fuse rating	10 A gG
Mechanical durability	30 Mcycles
Non-overlap time	1.5 Ms on energisation between NC and NO contact 1.5 ms on de-energisation between NC and NO contact
Mounting Location	Front
Connections - terminals	Screw clamp terminals1 0.00...0.00 in ² (1...2.5 mm ²) - rigid Screw clamp terminals2 0.00...0.00 in ² (1...2.5 mm ²) - rigid Screw clamp terminals1 0.00...0.00 in ² (1...2.5 mm ²) - flexible with or without cable end Screw clamp terminals2 0.00...0.00 in ² (1...2.5 mm ²) - flexible with or without cable end Screw clamp terminals AWG 10...AWG 18)
Tightening torque	10.62 Lbf.in (1.2 N.m) Philips No 2 10.62 lbf.in (1.2 N.m) flat Ø 6 mm

Environment

Environmental characteristic	Normal environment
Standards	IEC 60947-5-1 EN 60947-5-1 UL 60947-5-1
Product Certifications	UL[RETURN]CSA
IP degree of protection	IP20 conforming to VDE 0106
Protective treatment	TH IEC 60068
Ambient Air Temperature for Operation	23...140 °F (-5...60 °C)
Permissible ambient air temperature around the device	-40...158 °F (-40...70 °C) at U _c

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ambient Air Temperature for Storage	-76...176 °F (-60...80 °C)
Operating altitude	9842.52 ft (3000 m)

Ordering and shipping details

Category	22363-EASY TESYS DPER1
Discount Schedule	I13
GTIN	3606485332581
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.10 in (2.790 cm)
Package 1 Width	1.60 in (4.060 cm)
Package 1 Length	1.90 in (4.830 cm)
Package 1 Weight	1.06 oz (30.000 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	1.18 in (3.000 cm)
Package 2 Width	3.46 in (8.800 cm)
Package 2 Length	10.08 in (25.600 cm)
Package 2 Weight	12.28 oz (348.000 g)
Unit Type of Package 3	S02
Number of Units in Package 3	120
Package 3 Height	5.91 in (15.000 cm)
Package 3 Width	11.81 in (30.000 cm)
Package 3 Length	15.75 in (40.000 cm)
Package 3 Weight	8.25 lb(US) (3.744 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations