



KNIPEX Cobra® High-tech water pump pliers
DIN ISO 8976




87 01 125 
pliers grey atramentised, polished head, handles with non-slip plastic coating, the original in miniature




87 01 250 
pliers grey atramentised, polished head, handles with non-slip plastic coating




87 01 300 
pliers grey atramentised, polished head, handles with non-slip plastic coating




87 02 180 
pliers grey atramentised, polished head, handles with multi-component covers




87 02 250 
pliers grey atramentised, polished head, handles with slim multi-component covers



87 03 250 


chrome-plated pliers, handles with non-slip plastic coating



87 05 250 

chrome-plated pliers, handles with slim multi-component covers



87 05 300 

chrome-plated pliers, handles with multi-component covers



- Description
- Special
- Applications
- adjustment at the touch of a button directly on the workpiece
- fine adjustment for optimum adaptation to different size work pieces and a comfortable gripping position
- self-locking on pipes and nuts: no slipping on the workpiece and low handforce required
- gripping surfaces with special hardened teeth, teeth hardness approx. 61 HRC: low wear and reliable gripping
- box-joint design: high stability because of double guide
- reliable catching of the hinge bolt: no unintentional shifting
- pinch guard prevents operators' fingers being pinched
- Chrome vanadium electric steel, forged, oil-hardened

KNIPLEX Cobra® - the Hightech Water Pump Pliers. No more time-consuming test-adjusting of the correct opening size. Just position the upper jaw to the workpiece, push button and move close the lower jaw, ingeniously simple.



Fine adjustment by pushing a button: fast and comfortable









Fast and firm adjustment directly on the workpiece



Teeth set against the direction of rotation have a self-clamping effect and prevent slipping on the workpiece.





Product Number	EAN 4003773-				adjustment positions		
		Ø Inch	Ø mm	mm		mm	g
87 01 125	069935	1	27	27	13	125	85
87 01 150	060116	1 1/4	32	30	11	150	145
87 01 180	022015	1 1/2	42	36	18	180	170
87 01 250	022022	2	50	46	25	250	335
87 01 300	034087	2 3/4	70	60	30	300	530
87 02 180	042396	1 1/2	42	36	18	180	196
87 02 300	029144	2 3/4	70	60	30	300	580
87 02 250	040316	2	50	46	25	250	366
87 03 125	073949	1	25	27	13	125	85
87 03 180	005667	1 1/2	42	36	18	180	175
87 03 250	043805	2	50	46	25	250	314
87 03 300	041382	2 3/4	70	60	30	300	530
87 05 250	005681	2	50	46	25	250	355
87 05 300	014126	2 3/4	70	60	30	300	579

technical change and errors excepted