


Heavy duty grade power receptacles

Product description

2-pole, 3-wire grounding
30A, 125V/AC
30A, 250V/AC



Design features

- Heavy gauge galvanized steel mounting strap for corrosion resistance
- For use with copper or aluminum wire
- Flush receptacles fit one-gang or two-gang enclosures
- Surface receptacles have patented lay-in terminals that accept up to #4 AWG wire
- Surface receptacle backs feature concentric knockouts and an adjustable cord clamp to allow wiring from back or bottom



1263

Flush power NEMA TT



Rating A	V/AC	Description	Color	Catalog no.	
30	125	NEMA TT-30R flush mount power receptacle, matching plug 83	BK	□ 1263	•

Listed to UL498, file no. E15058; CSA certified to CSA C22.2, no. 42



1232

Flush power NEMA 5-30R & NEMA 6-30R



Rating A	V/AC	Description	Color	Catalog no.	
30	125	NEMA 5-30R flush mount power receptacle, matching plug S41	BK	□ 1233	•
30	250	NEMA 6-30R flush mount power receptacle, matching plug S42	BK	□ 1234	•

Listed to UL498, file no. E15058; CSA certified to C22.2, no. 42; NOM certified



U1263

Surface power receptacle



Rating A	V/AC	Description	Color	Catalog no.	
30	250	NEMA 6-30R surface mount power receptacle, matching plug S42	BK	□ 1232	•

Listed to UL498, file no. E15058; CSA certified to C22.2, no. 42; NOM certified

Panel power receptacles



Rating A	V/AC	Description	Color	Catalog no.	
30	125	NEMA TT-30R panel mount power receptacle, matching plug 83	BK	□ U1263	•

Listed to UL498, file no. E15058; CSA certified to C22.2, no. 42; NOM certified

Color ordering information:

BK (Black)



(Black)

Dimensional information: B-70 **Specification information:** Please visit www.cooperwiringdevices.com
Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page F-21