



Overview



Presentation	Reliable rack power distribution designed to increase manageability and efficiency in the data center The output and input connections are (10) C13 Real-time remote monitoring of connected loads User-defined alarms warn IT and data center managers of potential circuit overloads to prevent accidental power loss to critical equipment.
Lead time	Usually in Stock

General

Provided Equipment	Installation guide Rack Mounting brackets User Manual
--------------------	-------------------------------------------------------------

Physical

Cable length	12 ft (3.66 m)
Color	Black
Depth	3.03 in (7.7 cm)
Height	1.73 in (4.4 cm)
Product Weight	5.62 lb(US) (2.55 kg)
Width	17.52 in (44.5 cm)

Input

Line Rated Current	24 A
Permissible voltage	200...240 V
Max line current	30 A
Input current limits	30 A
Load Capacity	4992 VA
Input Frequency	50/60 Hz
Plug standard	NEMA L6-30P
Nominal Input Voltage	200 V 208 V 230 V

Output

Number of power socket outlets	10 IEC 60320 C13
--------------------------------	------------------

Conformance

Product Certifications	CUL Listed PSE UL Listed
Standards	UL 60950

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environmental

Ambient Air Temperature for Operation	23...113 °F (-5...45 °C)
Relative Humidity	5...95 %
Operating altitude	0...15000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	5...95 %
Storage altitude	0...50000 ft (0.00...15240.00 m)

Ordering and shipping details

GTIN	00731304272755
Package weight(Lbs)	8.02 lb(US) (3.64 kg)

Packing Units

Package 1 Height	6.73 in (17.1 cm)
Package 1 width	19.02 in (48.3 cm)
Package 1 Length	6.85 in (17.4 cm)
Number of Units in Package 3	1

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------