

OPTIONS & ACCESSORIES



AIRCRAFT CABLE



PENDANT MOUNT



HOOK MOUNT



WIREGUARD



MOTION SENSOR



RELOC® CORDS AND PLUGS

The I-BEAM Compact can be ordered with lamps, cord sets, RELOC® components and pre-wired occupancy sensors for fast installation.

ORDERING INFORMATION

For shortest lead times, configure product using **standard options (shown in bold)**.
Example: IBC 454L

IBC						
Series	Number of lamps/wattage	Distribution	Voltage	Ballast	Lamps installed ⁵	
IBC I-BEAM Compact	Lamps installed ¹	(blank) Narrow distribution with uplight	(blank) MVOLT (120V-277V)	T5HO	T5HO	
	454L 4-lamp, 54W, T5HO	NDS Narrow distribution with no uplight	HVOLT (347V-480V)	(blank) Program start 1.0 BF	(blank) F54T5HO/841	
	Unlamped	WD Wide distribution with uplight				
	454 4-lamp, 54W, T5HO	WDS Wide distribution no uplight				
Ballast configuration						
			(blank) One, four-lamp ballast		EL14 Emergency battery pack (1400 lumens) ³	
			2/2 Two, two-lamp ballasts		MSI Occupancy sensor-rewired ² (Aisle)	
Options						
					MSI360 Occupancy sensor-rewired ² (360°)	
					GLR Internal fast blow fusing ²	
					OCS OnePass® installed ²	
					FSP Integral side panels	
					IBPMP Pendant Monopoint ⁴	

Accessories (order as separate catalog number)	
IBAC120	Aircraft cable 10' Y hanger (1 pair)
WGIBC	Wireguard
HC36	Chain hanger, 36"
IBHMP	Hook monopoint ⁴

- NOTES:
- Lamps installed are F54T5HO/841 for T5HO.
 - Specify voltage.
 - UL Listed for 40°C ambient.
 - IBPMP must be ordered with fixture for channel modification. Splice box ships separately. Requires two ballasts.
 - Contact factory for additional T5HO lamp choices.



INDUSTRIAL FLUORESCENT | One Lithonia Way | Conyers, GA 30012 | Phone 800.315.4963 | www.lithonia.com/IBEAM

©2008 Acuity Brands Lighting, Inc. 03/08 IR7044 Form No. 160.002



Printed on paper containing 30% post consumer content