



LENOX® SNAP-BACK™ QUICK CHANGE ARBORS

TOOL-FREE BIT CHANGE

No allen key required to change LENOX® pilot bit*.

ANTI-JAM COLLAR

Reinforced collar drives hole saw without jamming or disengaging.

50% FEWER BREAKS**

Patent pending step bit design for less hole saw grabbing resulting in fewer pilot breaks.

UNIVERSAL HOLE SAW COMPATIBILITY

Accepts all threaded hole saws, no adapters required†.



* Only applies to LENOX® Pilot Drills
 ** vs previous generation LENOX® Pilot Drill drilling low carbon steel
 † For the Range of Diameters Listed On Packaging

STEP 1

Unlock Hole Saw

STEP 2

Unlock Pilot Bit



PROD NO	DESCRIPTION	COMPATIBLE HOLE SAW SIZES		SHANK SIZE	
		IN	MM	IN	MM
LXAH9912PBM	2L QC WITH STEP BIT PILOT DRILL	1-1/4" - 6"	31.8 - 152.4	1/2"	12.7
LXAH9938PBM	5L QC WITH STEP BIT PILOT DRILL	9/16" - 1-3/16"	14.3 - 30.2	3/8"	9.5
LXAH9912CPBM	2L QC WITH CARBIDE & SELF-FEED PILOT DRILL	1-1/4" - 6-1/4"	31.8 - 158.8	1/2"	12.7