



**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

K11A30U  
 7818103702611  
 TWO:6 STR-300 DUAL RATED  
 Active

**Web Use**  
 BURNDY Product Line

Width (in)  
 Length (in)  
 Height (in)  
 Thickness  
 D - in  
 Stud Size (Fraction)  
 N (in)

**Dimensional**

1.00  
 3.00  
 2.03  
 0.50  
 0.94  
 5/16  
 0.47

Number of Conductors  
 Number of Holes

**General**

2  
 2  
 Aluminum Universal Terminal, 1  
 Hole, Two: 6 AWG (Str)-300 kcmil,  
 5/16" Stud, 2 Screws, Al/Cu  
 Rated, Tin Plated

Product Description

**Conductor(s)**

Aluminum Size (Range)  
 Copper Solid Size (Range)  
 Copper Stranded (Range)

6 AWG-300 kcmil  
 4 AWG-4/0 AWG  
 6 AWG-300 kcmil

**Physical**

Installation Torque  
 Type of Plating  
 Connector Type  
 Plated (Yes or No)  
 Product Material

275  
 Tin  
 Terminal  
 Y  
 Aluminum

**Approvals / Certifications**

Rated for Direct Burial  
 UL Listed  
 CSA Certified  
 ROHS Compatible  
 Industry Standards

N  
 Y  
 Y  
 Exempt  
 UL468A-468B

**Documentation**

For further technical assistance, please contact us

**BURNDY LLC - USA**

47 East Industrial Park Drive  
 Manchester NH 03109

**BURNDY Technical Services**

47 East Industrial Park Drive  
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM  
 Monday - Friday  
 Phone: 800-346-4175