



# Nonmetallic Liquid Tight Conduit - Pre-wired Hook-up Kits

## Flexible PVC - Grey, NMLT Fittings, THHN Wire

### Features

- Resists corrosion, abrasion, oil, water, acid and rough environments.
- For direct burial and poured concrete
- Outdoor, sunlight resistant
- Ships complete with 1 x straight and 1 x 90° NMLT connector
- Temperature Range: -18°C to 80°C dry, 60°C wet, 75°C oil
- IP68 Rating - with Nesco P-series NMLT connectors (included)
- 6" wire lead

### Applications

- Air conditioner, heat pump hook-ups
- Applications rated to 600V
- Quick installation, cuts with a utility knife or PVC cutter

### Standard Material

- Integral Rigid and flexible PVC construction, cULus listed wire THHN

### Certification

- cULus Listed components



Catalog Number	UPC	NMLT Diameter	NMLT - Length (ft)	Wire - Length (ft)	MOQ	Non-Metallic Liquid Tight				
						Outside Diameter Min.	Outside Diameter Max.	Inside Diameter Min.	Inside Diameter Max.	Wall Thickness
ACW-4	5602	1/2"	4	5	1	0.69	0.71	0.484	0.504	0.21
ACW-6	15604	1/2"	6	7	1	0.82	0.84	0.622	0.642	0.21
ACW-8	15607	1/2"	8	9	1	1.03	1.05	0.82	0.84	0.21
ACW-6C	15606	1/2"	6	no wires	1	1.29	1.315	1.041	1.066	0.25
ACW07#8#10-6	15598	3/4"	6	7	1	1.63	1.66	1.38	1.41	0.25
ACW07#8#10-8	15599	3/4"	8	9	1	1.865	1.90	1.575	1.60	0.30

### Nesco Inc.

1039 Cardiff Blvd., Mississauga, ON L5S 1P4

TF: (866) 466-3726 Tel: (905) 793-2218

www.nescocanada.com