

Product data sheet

Characteristics

VH363BDSGL

Safety switch, heavy duty, fused, viewing window, Type 4X, 600V, 100A, 3 pole, neutral bonded, ground lugs



Main

| | |
|---------------------------|--|
| Product | Single Throw Safety Switch |
| Duty Rating | Heavy duty |
| Device Application | Heavy application |
| Disconnect Type | Fusible disconnect |
| Factory Installed Neutral | Neutral (factory bonded) |
| Number of Poles | 3 |
| Current Rating | 100 A |
| Voltage Rating | 600 V AC/DC |
| Enclosure Rating | NEMA 4X stainless steel 304 |
| Motor power hp | 25 Hp at 480 V AC 50-60 Hz for 3 phase motors 60 Hp at 480 V AC 50-60 Hz for 3 phase motors 30 Hp at 600 V AC 50-60 Hz for 3 phase motors 100 Hp at 600 V AC 50-60 Hz for 3 phase motors 50 hp at 600 V DC |

Complementary

| | |
|-----------------------|--|
| Short-circuit current | 200 kA for J |
| Fuse type | J |
| Mounting Type | Surface |
| Electrical Connection | Lugs |
| Wiring configuration | 4-wire (3PH + N) |
| Wire Size | AWG 12...AWG 1/0 aluminium AWG 14...AWG 1/0 copper |
| Tightening torque | 50 Lbf.In (5.65 N.m) (AWG 1...AWG 3/0) 45 Lbf.In (5.08 N.m) (AWG 6...AWG 4) 40 Lbf.In (4.52 N.m) 0.01 in ² (8.367 mm ²) (AWG 8) 35 lbf.in (3.95 N.m) 0.00...0.01 in ² (2.06...5.261 mm ²) (AWG 14...AWG 10) |
| Depth | 7.2 in (182.88 mm) |
| Width | 9.336 in (237.13 mm) |
| Height | 20.73 in (526.54 mm) |
| Net Weight | 22.99 lb(US) (10.43 kg) |
| Grounding Kit | Factory installation |
| Service Entrance | Suitable service entrance for Canada |

Environment

| | |
|----------------|----------------------|
| Certifications | UL listed file E2875 |
|----------------|----------------------|

Ordering and shipping details

| | |
|-------------------|----------------------------------|
| Category | 00010-H&HU SW,2&3P,N4,SS,30-200A |
| Discount Schedule | DE1 |
| GTIN | 3606485894171 |
| Returnability | No |
| Country of origin | US |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

| | |
|------------------------------|------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 7.50 in (19.05 cm) |
| Package 1 Width | 11.37 in (28.892 cm) |
| Package 1 Length | 22.62 in (57.467 cm) |
| Package 1 Weight | 24.03 lb(US) (10.9 kg) |

Offer Sustainability

| | |
|---------------------------|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| EU RoHS Directive | Under investigation |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |