




Canadian WireTwist™ CU/AL Wire Connector



Features

- Only aluminum-to-copper twist-on connector specifically designed to provide a secure connection while preventing aluminum corrosion
- Specially formulated corrosion-resistant compound cuts and penetrates corrosion build-up on aluminum conductors for increased conductivity and cooler connections
- Deep skirt provides maximum dielectric strength
- Shell rated for 105° C
- CSA Certified

Models Dimensions

Model	A	B	C	D	E	
65 Purple	17/64 in., 7 mm	13/32 in., 10.5 mm	13/16 in., 21 mm	35/64 in., 14 mm	1-11/64 in., 34 mm	

Model	Color	Wire Combination Range (Inches)	Quantity	Cat. No.
CCUAL	Purple	600Volt*		
		1 #10 AL sol. w/1 or 2 #10 CU sol. 1 #10 AL w/1 or 2 #12 CU 1 #10 AL w/1 or 2 #14 CU 1 #10 AL w/1 or 2 #16 CU 2 #10 AL sol. w/1 #12 CU 2 #10 AL sol. w/1 #14 CU 2 #12 AL sol. w/1 #10 CU sol. 2 #12 AL sol. w/1 #10 CU str. 1 #12 AL sol. w/1 or 2 #10 CU sol or str	Card of 15	30-1CCUAL
		1 #12 AL str. w/1 or 2 #10 CU sol. 1 #12 AL w/1 or 2 #12 CU 2 #12 AL sol. w/1 #12 CU 1 #12 AL w/1 or 2 #14 CU 2 #12 AL sol. w/1 #14 CU 1 #10 AL w/1 or 2 #18 CU 2 #10 AL sol. w/1 #16 CU 2 #10 AL sol. w/1 #18 CU 1 #12 AL w/1 or 2 #16 CU 1 #12 AL w/1 or 2 #18 CU 2 #12 AL sol. w/1 #16 CU 2 #12 AL sol. w/1 #18 CU	Jar of 75	30-2CCUAL
			Jar of 300	30-3CCUAL