



**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

K2A40U2N  
 7818106004055  
 TWO:300-800 NEMA  
 Active

**Web Use**  
 BURNDY Product Line

**Dimensional**

Width (in) 3.19  
 Length (in) 4.75  
 Bolt Hole Size (in) 0.50  
 Thickness 0.50  
 D - in 3.03  
 Pad Width (in) 3.20  
 E - in 1.75  
 N (in) 0.63

**General**

Number of Conductors 2  
 Number of Holes 2  
 Product Description Aluminum Universal Terminal, 2 Conductor, 2 Hole, 300-800 kcmil, 1/2" Stud, 1.75" Stud Hole Spacing, 2 Screws, Al/Cu Rated, Tin Plated


**Conductor(s)**

Aluminum Size (Range) 300 - 800 kcmil  
 Copper Solid Size (Range) N/A  
 Copper Stranded (Range) 300 kcmil-800 kcmil

**Physical**

Installation Torque 375  
 Type of Plating Tin  
 Connector Type Terminal  
 Bolt Hole Size 1/2  
 Plated (Yes or No) N  
 Product Material Aluminum

**Approvals / Certifications**



Rated for Direct Burial	N
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Non-Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B
<b>Documentation</b>	

**For further technical assistance, please contact us**

**BURNDY LLC - USA**

47 East Industrial Park Drive  
Manchester NH 03109

**BURNDY Technical Services**

47 East Industrial Park Drive  
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM  
Monday - Friday  
Phone: 800-346-4175