


# IDEAL® STRIPMASTER® WIRE STRIPPERS

## Stripmaster® and Stripmaster® Lite Wire Strippers



- One-step stripping enhances productivity
- Spring-action motion increases leverage and reduces operator fatigue
- Precision-ground, knife-type blades provide clean, accurate stripping
- Sturdy die-cast frame provides long-term durability
- Wire gripper holds wire securely in position
- Stripmaster® Lite designed for smaller hands – 3/4 the size of the standard Stripmaster®



Gripper holds the wire securely in position.

Knife-type stripping blades have form-ground holes which penetrate the insulation like a knife, giving a clean insulation cut.



Stripmaster® Wire Stripper



Stripmaster® Lite Wire Stripper

### Stripmaster® Wire Strippers and Knife-Type Blades

| Specifications — Stripping Hole Diameter in Inches (mm) |                |               |               |               |               |               |               |               |               |               |               |               | Cat. No.            | Replacement Blades (Pair) Cat. No. | Replacement Frame Cat. No. |
|---|----------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------------|------------------------------------|----------------------------|
| Wire Size AWG   |                |               |               |               |               |               |               |               |               |               |               |               |                     |                                    |                            |
| 6   | 8              | 10            | 12            | 14            | 16            | 18            | 20            | 22            | 24            | 26            | 28            | 30            |                     |                                    |                            |
|   | 0.159<br>(4.0) | .141<br>(3.6) | .106<br>(2.7) |               |               |               |               |               |               |               |               |               | 45-090* or 45-290** | L-4419                             | L-5620                     |
|   |                | .144<br>(3.6) | .105<br>(2.7) | .085<br>(2.2) | .073<br>(1.8) | .073<br>(1.8) |               |               |               |               |               |               | 45-091              | L-4420                             | L-5620                     |
|   |                | .144<br>(3.6) | .113<br>(2.9) | .090<br>(2.3) | .072<br>(1.8) | .061<br>(1.5) | .048<br>(1.2) | .048<br>(1.2) |               |               |               |               | 45-092* or 45-292** | L-4421                             | L-5620                     |
|   |                |               |               | .090<br>(2.3) | .072<br>(1.8) | .061<br>(1.5) | .039<br>(1.0) | .039<br>(1.0) |               |               |               |               | 45-093              | L-4422                             | L-5620                     |
| .230<br>(2.3)   | .198<br>(5.0)  |               |               |               |               |               |               |               |               |               |               |               | 45-096              | L-4453                             | L-4453                     |
|   |                |               |               |               | .072<br>(1.8) | .061<br>(1.5) | .048<br>(1.2) | .039<br>(1.0) | .032<br>(0.8) | .026<br>(0.7) |               |               | 45-097              | L-4994                             | L-5620                     |
|   |                |               |               |               |               |               | .048<br>(1.2) | .039<br>(1.0) | .032<br>(0.8) | .026<br>(0.7) | .021<br>(0.5) | .016<br>(0.4) | 45-098              | L-5361                             | L-5620                     |
|   | .198<br>(5.0)  | .167<br>(4.2) |               |               | .062<br>(1.6) | .055<br>(1.4) |               |               |               |               |               |               | 45-099              | L-8763                             | L-5620                     |

\*Boxed \*\* Blister Card Tolerances +001 - .005

### Stripmaster® Lite Wire Strippers and Knife-Type Blades

| Specifications — Stripping Hole Diameter Inches (mm) |               |               |               |   |               |               |               |               |               | Cat. No. | Replacement Blades (Pair) Cat. No. | Replacement Frame Cat. No. |
|--|---------------|---------------|---------------|---|---------------|---------------|---------------|---------------|---------------|----------|------------------------------------|----------------------------|
| Wire Size AWG  |               |               |               |   |               |               |               |               |               |          |                                    |                            |
| 12   | 14            | 16            | 18            | 20  | 22            | 24            | 26            | 28            | 30            |          |                                    |                            |
|  |               | .072<br>(1.8) | .061<br>(1.5) | .048<br>(1.2)                             | .039<br>(1.0) |               |               |               |               | 45-671   | LB-1001                            | LB-1421                    |
|  |               |               |               |   |               | .032<br>(0.8) | .026<br>(0.7) | .021<br>(0.5) | .016<br>(0.4) | 45-672   | LB-1002                            | LB-1421                    |
| .113<br>(2.09)                                       | .090<br>(2.3) | .072<br>(1.8) | .061<br>(1.5) | All stranded wire                         |               |               |               |               |               | 45-673   | LB-1003                            | LB-1421                    |
| .096<br>(2.4)  | .085<br>(2.2) | .073<br>(1.9) | .061<br>(1.5) | 12 & 14 Solid Wire, 16 & 18 Stranded Wire |               |               |               |               |               | 45-674   | LB-1004                            | LB-1421                    |

Tolerances +001 - .005